




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04N	A2	(11) International Publication Number: WO 96/21990 (43) International Publication Date: 18 July 1996 (18.07.96)
(21) International Application Number: PCT/US96/00246 (22) International Filing Date: 3 January 1996 (03.01.96) (30) Priority Data: 08/367,997 3 January 1995 (03.01.95) US (71) Applicant: SCIENTIFIC-ATLANTA, INC. [US/US]; One Technology Parkway South, Norcross, GA 30092 (US). (72) Inventors: HOUSER, Peter, B.; 14574 High Pine Street, Poway, CA 92064 (US). SCHUTTE, Mark, E.; 4570 Browning Trail, Sugar Hill, GA 30518 (US). MAGID, Gloria, J.; 13810 Riverhead Court, San Diego, CA 92129 (US). (74) Agents: SHEA, Michael, J. et al.; Banner & Allegretti, Ltd., 11th floor, 1001 G Street N.W., Washington, DC 20001 (US).		(81) Designated States: AL, AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AZ, BY, KZ, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>

(54) Title: INFORMATION SYSTEM HAVING A SPEECH INTERFACE**(57) Abstract**

A system for controlling a device and for controlling access to broadcast information is disclosed. The system includes a first receiver for receiving utterances of a speaker, a second receiver for receiving vocabulary data defining a vocabulary of utterances, and a processor for executing a speech recognition algorithm using the received vocabulary data to recognize the utterances of the speaker and for controlling the device and the access to the broadcast information in accordance with the recognized utterances of the speaker.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Larvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

INFORMATION SYSTEM HAVING A SPEECH INTERFACE

BACKGROUND OF THE INVENTION

1. Technical Field

The present invention generally relates to an information system having a speech interface and, more particularly, to a subscription information system including a subscriber terminal unit which provides for control of electronic devices and access to information services by spoken commands.

2. Description of the Related Art

The volume of information and number of features being made available to subscribers in information systems such as subscription television systems are continuously increasing. For example, the advent of optical fiber networks and links to telecommunication networks enables an almost limitless supply of information and features to be provided to subscribers. Already subscription television systems are being used for addressed message transmissions, pay-per-view programming, impulse pay-per-view programming, favorite channel features, and parental control. Cable television system operators may also provide text services such as news articles, sports scores, stock market quotations, and weather reports. Relatively new features such as video game delivery, wide area network access, home shopping, travel reservations service, home banking, energy management, video conferencing and other such services are also being provided.

-2-

Recently, some companies have begun offering electronic television schedules for purchase by subscription television providers who, in turn, provide the schedules to their subscribers. The schedules contain a listing of television programs by time and channel, and are typically displayed as a grid on the television screen. Such a system is shown in PCT Publication No. WO 92/04801, applied for by Insight Telecast, Inc. (hereinafter "the Insight system") and incorporated herein by reference. That publication describes a display system for maneuvering a cursor through a television schedule. The system also describes that a subscriber can choose a program for recording by moving a cursor to the selected program; the system will automatically program the subscriber's video cassette recorder.

Also recently, so-called near-video-on-demand services have been introduced. These services provide a simulation of the videotape rental experience. One such system is described in Walter, U.S. Patent No. 5,168,353, incorporated herein by reference. Walker describes in column 4, lines 18-27 that a converter may be enabled to descramble two channels carrying the same program at staggered intervals. This allows returning to the same portion of the video after a pause equal to the staggered time interval. The Walker patent gives as an example a subscriber ordering a program that begins at 8:00 p.m. The converter unscrambles the 8:00 showing as well as the 8:15 showing so that the viewer may return to the same point in the program after a fifteen minute break.

This increase in information and features has generally resulted in a corresponding increase in the complexity of the subscriber's interface with the system. Since the subscriber's "comfort level" with an interface for accessing information and features will often determine

-3-

whether the subscriber will utilize the information and features, there is a need for user-friendly interfaces. An interface such as that described in commonly assigned copending Application Serial No. 07/800,836 entitled "Method and Apparatus for Providing an On-Screen User Interface for a Subscription Television Terminal", incorporated herein by reference, can greatly enhance the ability of a user to access available features. The system described in that application significantly reduces the number of key presses and data entries required to utilize available features; moreover, a key pad is designed in such a way as to group keys together in a manner to facilitate their use. However, even with such an improved interface, certain tasks are simply not well-suited for execution using a keypad on a subscriber terminal unit or an associated remote control. For example, while a subscriber might be very interested in using an EPG to determine the channel number and time for the next showing of a particular television show or to find all movies being shown in the next week starring a particular actress, such tasks are not easily implemented using menu screens and key presses.

SUMMARY OF THE INVENTION

The present invention adds a speech recognition interface to a subscriber terminal unit in an information system for implementing spoken control of electronic devices at the subscriber location and of access to information transmitted to the subscriber terminal unit. The speech recognition interface enhances the interface of the subscriber with the information system by allowing control using language which is naturally spoken by the subscriber. Such natural language control affords ease of use as well as permitting the implementation of tasks which are not easily implemented using menu screens and key presses.

-4-

In accordance with one aspect of the instant invention, a system for controlling a device includes a first receiver for receiving utterances of a speaker, a second receiver for receiving vocabulary data defining a vocabulary of utterances, and a processor for executing a speech recognition algorithm using the received vocabulary data to recognize the utterances of the speaker and for controlling the device in accordance with the recognized utterances of the speaker.

In accordance with another aspect of the invention, a method for controlling a device includes the steps of receiving utterances of a speaker, receiving vocabulary data defining a vocabulary of utterances, using the received vocabulary data to recognize the utterances of the speaker, and controlling the device in accordance with the recognized utterances of the speaker.

In accordance with another aspect of the invention, a system for controlling access to broadcast information includes a first receiver for receiving utterances of a speaker, a second receiver for receiving vocabulary data defining a vocabulary of utterances, and a processor for executing a speech recognition algorithm using the received vocabulary data to recognize the utterances of the speaker and for controlling access to the broadcast information in accordance with the recognized utterances of the speaker.

In accordance with another aspect of the invention, a method for controlling access to broadcast information includes the steps of receiving utterances of a speaker, receiving vocabulary data defining a vocabulary of utterances, using the received vocabulary data to recognize the utterances of the speaker, and controlling access to the broadcast information in accordance with the recognized utterances of the speaker.

-5-

In accordance with yet another aspect of the invention, a system for controlling a device and for controlling access to broadcast information includes a first receiver for receiving utterances of a speaker, a second receiver for receiving vocabulary data defining a vocabulary of utterances, and a processor for executing a speech recognition algorithm using the received vocabulary data to recognize the utterances of the speaker and for controlling the device and the access to the broadcast information in accordance with the recognized utterances of the speaker.

In accordance with yet another aspect of the invention, a method for controlling a device and for controlling access to broadcast information includes the steps of receiving utterances of a speaker, receiving vocabulary data defining a vocabulary of utterances, using the received vocabulary data to recognize the utterances of the speaker, and controlling the device and the access to the broadcast information in accordance with the recognized utterances of the speaker.

In accordance with yet another aspect of the invention, a system for controlling a device includes a transmitter for transmitting vocabulary data for defining a vocabulary of utterances; and a terminal unit including a first receiver for receiving utterance data of a speaker, a second receiver for receiving the transmitted vocabulary data, and a processor for executing a speech recognition algorithm using the received vocabulary data to recognize utterances of the speaker and for controlling said device in accordance with the recognized utterances of the speaker.

In accordance with yet another aspect of the invention, a method for controlling a device includes the steps of transmitting vocabulary data for defining a vocabulary of utterances, receiving utterance data of a speaker, receiving the transmitted vocabulary data, using the

-6-

received vocabulary data to recognize utterances of the speaker, and controlling the device in accordance with the recognized utterances of the speaker.

In accordance with still another aspect of the invention, a system for controlling access to broadcast information includes a transmitter for transmitting vocabulary data defining a vocabulary of utterances and a terminal unit including a first receiver for receiving utterance data of a speaker, a second receiver for receiving the transmitted vocabulary data, and a processor for executing a speech recognition algorithm using the received vocabulary data to recognize utterances of the speaker and for controlling access to the broadcast information in accordance with the recognized utterances of the speaker.

In accordance with still another aspect of the invention, a method for controlling access to broadcast information includes the steps of transmitting vocabulary data for defining a vocabulary of utterances, receiving utterance data of a speaker, receiving the transmitted vocabulary data, using the received vocabulary data to recognize utterances of the speaker, and accessing the information in accordance with the recognized utterances of the speaker.

In accordance with still another aspect of the invention, a system for controlling a device and for controlling access to broadcast information includes a transmitter for transmitting vocabulary data defining a vocabulary of utterances and a terminal unit including a first receiver for receiving utterance data of a speaker, a second receiver for receiving the transmitted vocabulary data, and a processor for executing a speech recognition algorithm using the received vocabulary data to recognize utterances of the speaker and for controlling the device and the access to the broadcast information in accordance with the recognized utterances of the speaker.

-7-

In accordance with still another aspect of the invention, a method for controlling a device and for controlling access to broadcast information includes the steps of transmitting vocabulary data for defining a vocabulary of utterances, receiving utterance data of a speaker, receiving the transmitted vocabulary data, using the received vocabulary data to recognize utterances of the speaker, and controlling the device and the access to the information in accordance with the recognized utterances of the speaker.

In accordance with still another aspect of the invention, a system for controlling a television receiver to allow user selection of broadcast programs from program schedule information includes a first receiver for receiving the program schedule information, a second receiver for receiving utterances of a user, and a processor for executing a speech recognition algorithm to recognize the utterances of the user and for selecting broadcast programs from the program schedule information in accordance with the recognized utterances of the user.

In accordance with another aspect of the invention, a remote control for transmitting utterance data to a receiver includes a microphone for receiving utterances of a speaker, an analog-to-digital converter for converting utterance signals from the microphone to digital utterance signals, a digital signal processor for extracting time-variant spectral characteristics of the digital utterance signals, and a transmitter for transmitting the time-variant spectral characteristics to the receiver.

In accordance with still another aspect of the invention, a subscription television system includes a head-end installation for transmitting vocabulary data for defining a vocabulary of spoken commands and a subscriber terminal unit connected to a television. The subscriber

-8-

terminal unit includes a first receiver for receiving spoken command data, a second receiver for receiving the vocabulary data transmitted from the head-end installation, and a processor for executing a speech recognition algorithm using the vocabulary data to recognize spoken commands and for controlling the television in accordance with the recognized spoken commands.

In accordance with another aspect of the invention, an information broadcasting center for broadcasting information to at least one terminal unit includes a first transmitter for transmitting text information and a second transmitter for transmitting phonemic data corresponding to at least a portion of the text information.

In accordance with another aspect of the invention, a subscriber terminal unit includes a tuner for tuning channels of a television signal, each channel carrying a respective program identified by a program title, a memory for storing a speech recognition algorithm for recognizing spoken program titles, and a processor for executing the speech recognition algorithm to recognize a program title spoken by a subscriber and for generating a tuner control signal for controlling the tuner to tune to the channel carrying the program corresponding to the recognized program title.

These and other features and advantages of the present invention will be better understood from a reading of the following detailed description in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

-9-

Figure 1 is a generalized block diagram of an information system in accordance with the instant invention.

Figures 2A, 2B, and 2C are a block diagram of a subscription television system in which the instant invention is implemented.

5 Figure 3 is a detailed block diagram of subscriber terminal unit 160 shown in Figure 2C.

Figure 4 is a block diagram of a first hardware arrangement of the speech recognition interface of the instant invention.

Figure 5 is a block diagram of a second hardware arrangement of the speech recognition interface of the instant invention.

10 Figure 6 is a block diagram of a third hardware arrangement of the speech recognition interface of the instant invention.

Figure 7 is a block diagram of a fourth hardware arrangement of the speech recognition interface of the instant invention.

15 Figure 8 is a block diagram of a fifth hardware arrangement of the speech recognition interface of the instant invention.

Figure 9 is an illustration of remote control 166 shown in Figure 2C.

Figure 10 is a diagram of a volume line bar.

Figure 11 is a diagram of an electronic programming guide grid.

20 Figures 12A-12U are diagrams illustrating screens generated during the speech recognition operation.

-10-

Figures 13A-13G are diagrams illustrating additional screens generated during the speech recognition operation.

Figure 14 is a diagram illustrating an additional screen generated during the speech recognition operation.

5 Figure 15 is a block diagram of another system in which the speech recognition interface of the instant invention may be utilized.

DETAILED DESCRIPTION

The following conventions will be used throughout this detailed description. The < > symbols will be used to denote keypad commands input via the keypads to be described below, e.g., <Enter>. Quotation marks and capital letters will be used to designate spoken commands, e.g., "RECORD" or "POWER ON". Capital letters and italics will be utilized to indicate variables such as channel numbers, etc.

Figure 1 is a generalized block diagram of an information system 10 in accordance with the instant invention. Information system 10 includes an information distribution center 12 which receives information from one or more remotely located information providers 14-1, ..., 14-n and supplies or broadcasts this information to a terminal unit 16. "Information" as used herein includes, but is not limited to, analog video, analog audio, digital video, digital audio, text services such as news articles, sports scores, stock market quotations, and weather reports, electronic messages, electronic program guides, database information, software including game programs, and wide area network data. Alternatively or in addition, information distribution

15
20

-11-

center 12 may locally generate information and supply this locally generated information to terminal unit 16.

The information transmitted by information distribution center 12 to terminal unit 16 includes vocabulary data representative of a vocabulary of spoken sounds or words ("utterances"). This vocabulary provides, for example, for spoken control of a device 18 and for spoken control of access to the information transmitted by information distribution center 12. Specifically, terminal unit 16 receives vocabulary data from information distribution center 12 and speech ("utterance") data from a user. Terminal unit 16 includes a processor for executing a speech recognition algorithm for comparing the vocabulary data and the spoken command data to recognize, for example, commands for controlling device 18 or commands for accessing information transmitted by information distribution center 12. Terminal unit 16 then appropriately generates a command for controlling device 18 or for accessing information transmitted by information distribution center 12. As used herein, a speech recognition algorithm refers to an algorithm which converts spoken audio input into text or corresponding commands. A speaker verification algorithm refers to an algorithm which verifies the claimed identity of a speaker based upon a sample of the claimant's speech. A speaker identification algorithm refers to an algorithm which identifies a speaker from a list of previously sampled alternatives based upon audio input from a speaker. A speaker identification algorithm may be used, for example, to limit the ability to control the device and/or access information to particular speakers.

-12-

The vocabulary data transmitted from information distribution center 12 to terminal unit 16 may, for example, be phoneme data. A phoneme is a member of the set of the smallest units of speech that serve to distinguish one utterance from another in a language or dialect. Each sound or spoken word in the vocabulary may thus be represented by a combination of phonemes.

5 Alternatively, the vocabulary data may be template data generated by having a person or persons speak each sound or word. Each spoken sound or word in the vocabulary may thus be represented by a respective corresponding template. It should be noted that although the system of Figure 1 illustrates a system in which information from information providers 14-1, ..., 14-n and the vocabulary data are transmitted over the same communication link, the invention is not
10 limited in this respect. Thus, information from information service providers 14-1, ..., 14-n and the vocabulary data may be transmitted over different communications links.

Many different arrangements may be utilized to provide the speech data to terminal unit 16. In a first illustrative, but non-limiting, arrangement, a remote control is provided which includes a wireless microphone or related transducer for transmitting sounds or words spoken
15 by a user to terminal unit 16 via electrical, optical, or radio frequency signals. Terminal unit 16 then includes a receiver, an analog front end for conditioning the received signal, a codec for performing an analog-to-digital conversion of the conditioned signal, and an interface circuit for interfacing to the processor. By conditioning is meant noise cancellation, noise reduction, filtering, and other known techniques for, for example, modifying a received electrical signal
20 originating from a voice transducer. In a second illustrative arrangement, a remote control is provided with a microphone, an analog receiver for conditioning the sound signal from the

-13-

microphone, a codec for performing an analog-to-digital conversion of the conditioned signal, and a transmitter for transmitting the digitized sound data signal to terminal unit 16 using, for example, infrared or radio frequency signals. Terminal unit 16 then includes a receiver for receiving the digitized sound data signal and an interface circuit for interfacing to the processor.

5 The digitized sound data signal will typically require a data transfer rate of at least 64k bits per second. In a third illustrative arrangement, a remote control is provided with a microphone, an analog receiver for conditioning the sound signal from the microphone, a codec for performing an analog-to-digital conversion of the conditioned signal, a digital signal processor for analyzing the digitized sound signal to extract spectral data, and a transmitter for transmitting the spectral data to terminal unit 16 using, for example, infrared signals. Terminal unit 16 then includes a receiver for receiving the spectral data and an interface circuit for interfacing to the processor. Because spectral data is transmitted in this third arrangement as opposed to the digitized sound data in the second arrangement, the data rate is much lower, i.e., less than 10k bits per second. Because spectral analysis is performed in the remote control, the loading of the processor of terminal unit 16 is reduced during the recognition operation by 30-50% as compared with the second arrangement. In a fourth illustrative arrangement, terminal unit 16 is provided with a microphone, an analog front end to condition the sound signal from the microphone, a codec to perform an analog-to-digital conversion of the conditioned signal, and an interface circuit for interfacing to the processor. In a fifth illustrative arrangement, terminal unit 16 is provided with a microphone, an analog front end to condition the sound signal from the microphone, a codec to perform an analog-to-digital conversion of the conditioned signal, a digital signal processor

-14-

for analyzing the digitized sound signal to extract spectral data, and an interface circuit for interfacing to the processor bus. The digital signal processor in the fifth arrangement is used to lower loading on the processor of terminal unit 16 as compared with the fourth arrangement. These various arrangements are illustrative only and other arrangements may be utilized to provide speech data to terminal unit 16 within the scope of the instant invention.

The vocabulary data transmitted by information distribution center 12 may define commands which a user may speak to control device 18. Device 18 may be any device which is capable of being operated in response to user-supplied commands and the instant invention is not limited in this respect. Thus, device 18 may be, for example, a television, a stereo receiver, a video cassette recorder, an audio cassette recorder, a compact disc (CD) player, a video disc player, a video game player, or a computer. As an illustration, assume that device 18 is a television which is plugged into a switched power outlet of terminal unit 16 and that it is desired to allow a user to control the on and off switching of the television by speaking the commands "POWER ON" and "POWER OFF", respectively. Information distribution center 12 would then transmit to terminal unit 16 phonemic or template vocabulary data defining a command vocabulary having the words POWER, ON, and OFF. When the user says either "POWER ON" or "POWER OFF" and the speech data corresponding to the command is provided to terminal unit 16 using any of the arrangements described above, the processor of terminal unit 16 executes the speech recognition algorithm to compare the spoken command with the phonemic or template data representing the command vocabulary in order to recognize the spoken command. Terminal unit 16 then appropriately controls device 18, i.e., either switching the

-15-

television on or off. Since the television is plugged into a switched power outlet of terminal unit 16 as described above, the on and off switching of the television is implemented internally to terminal unit 16. However, the instant invention is also applicable to situations where the recognized command is passed to device 18 for execution via a communication link. Such a communication link may, for example, be an infrared link, an RF link, a coaxial cable, a telephone network, a satellite system, or an optical fiber and the invention is not limited in this respect.

The vocabulary data may alternatively or additionally define words and commands which a user may speak to access information transmitted from information distribution center 12. This feature permits a user to perform tasks which would be very difficult to perform with a menu driven user interface. For example, this feature can be used to perform a keyword search of the titles of news articles transmitted from information distribution center 12 using a "SEARCH KEYWORDS" command. Specifically, information distribution center 12 determines which individual words are to serve as the keywords and generates a phonemic or template "dictionary" which maps these keywords to phonemes or templates. Information distribution center 12 transmits the news articles and the dictionary to terminal unit 16 where they are stored in memory. For each keyword, terminal unit 16 generates the corresponding phonemic or template string using the dictionary. The string is then "registered" with the speech recognition algorithm as a single recognizable utterance, i.e, it becomes a basic part of the speech recognition algorithm's vocabulary. The registration includes specifying an identifier for the phonemic or template string which could be a numerical value or the keyword itself. When the

-16-

user then speaks the "SEARCH KEYWORDS" command, a display dedicated to this command is provided, for example, on a display device associated with terminal unit 16 or on a television connected to terminal unit 16. The user may then speak a command "ONLY *KEYWORD*" to limit the search by terminal unit 16 to news articles transmitted by information distribution center 12 having the spoken *KEYWORD* in the title. The user may then speak additional keywords to refine the search or may view the news articles having the spoken keyword in the title. It can readily be seen that performing such a task using a conventional menu driven user interface would be extremely difficult.

Information distribution center 12 may also transmit to terminal unit 16 grammar information which specifies how the words and commands may be used. For example, "POWER ON" might be an allowable command, but "ON POWER" might not. The grammar information may also include context-specific rules. For example, "RECORD" might be allowed only when a VCR is present and turned on. It should be noted that some or all of the grammar and context specific rules may be permanently stored in memory of terminal unit 16.

Figures 2A, 2B, and 2C are a block diagram of a subscription television system 100 in which the instant invention is incorporated. It will of course be apparent that the instant invention may be applied to information systems other than a subscription television system and the invention is not limited in this respect. A subscription television system 100 provides information to a plurality of subscriber locations, e.g., 120-1, ..., 120-n (see Figure 2C). The information may include, but is not limited to analog video, analog audio, digital video, digital audio, text services such as news articles, sports scores, stock market quotations, and weather

-17-

reports, electronic messages, electronic program guides, database information, software including game programs, and wide area network data. Referring to Figure 2A, subscription television system 100 includes a plurality of information providers 114-1, ..., 114-n each of which may supply one or more of the information types identified above. For example, 5 information provider 114-2 includes an information source 115 for providing an analog television signal to a transmitter 118. Transmitter 118 is coupled to a satellite uplink 121 which transmits an analog television signal 122-2. Information providers 114-1 and 114-3 each provide digital information from an information source 115 to a respective encoder 116 that generates an encoded data stream for transmission. Information source 115 of information providers 114-1 10 and 114-3 may be a memory such as an optical memory for storing information. If either of information providers 114-1 and 114-3 provides a variety of information, e.g., a plurality of different game programs or different types of text services or a plurality of digital television or audio programs, encoder 116 may multiplex the information to generate a multiplexed data stream for transmission. The data stream from encoder 116 is supplied to a transmitter 118 and 15 then to a satellite uplink 121. By way of example in Figure 2A, the encoder 116 operated by information provider 114-1 generates a digital data signal 122-1 and the encoder 116 operated by information provider 114-3 generates a digital data signal 122-3. Each signal 122-1, 122-2, and 122-3 is transmitted via a satellite 123 to a head-end installation 125 (see Figure 2B). It is understood that there may be many information providers in the system of the instant invention, 20 and therefore a plurality of signals may be transmitted via satellite 123 to locations such as head-end installation 125. Although not shown, signals may be received at locations other than a

-18-

head-end installation, such as, for example, at the locale of a direct broadcast satellite (DBS) subscriber. In addition, while the link between the information providers and the head-end installation is shown as a satellite link, the invention is not limited in this respect. Accordingly, this link may, for example, be a coaxial cable, a telephone network, a satellite system, a radio
5 frequency (RF) link, or an optical fiber or any combination thereof. Further, while the information providers of Figure 2A are remotely located from head-end installation 125, one or more information providers may be physically located at the same site as head-end installation 125.

Referring to Figure 2B, a satellite down-link 124 at head-end installation 125 provides
10 received signals 122-1, 122-2, and 122-3. Head-end installation 125 serves as a communications hub, interfacing to the various information providers, and connecting them on a conditional basis to subscriber locations 120-1, ..., 120-n. For example, received digital data signal 122-1 is supplied to a receiver 126-1 and then to a modulator 128-1, where it is modulated onto a distinct cable channel. Modulator 128-1 may employ any suitable modulation technique such as
15 quadrature partial response (QPR) modulation. Received analog television signal 122-2 is supplied to a receiver 126-2, then to a scrambler 130 for scrambling, and then to a modulator 128-2, where it is modulated into a distinct cable channel. As will be discussed in detail below, scrambler 130 also inserts in-band data into analog television signal 122-2. It will be apparent that additional receivers, modulators, and, optionally, scramblers may be similarly provided for
20 digital and analog information signals received from other information providers, either local or remote (not shown).

-19-

Received digital data signal 122-3 is provided to an information signal processor (ISP) 142 so that it may be transmitted using so-called in-band or out-of-band transmissions. Other data streams (not shown) from other information providers may also be provided to ISP 142. ISP 142 is responsible for receiving the one or more data signals and then transmitting data to the subscriber terminal locations as will now be described. ISP 142 provides data to scrambler 130. ISP 142 may provide data to additional scramblers depending on factors such as the amount of data to be transmitted and the speed at which the data must be supplied and updated. Data is repetitively sent out by scrambler 130. If there is only one scrambler and a large amount of data, the repetition rate will be slow. Use of more than one scrambler allows the data repetition rate to increase.

Specifically, scrambler 130 places data in-band for transmission to subscribers, along with scrambling the associated analog television signal 122-2. In one arrangement, data is placed in the vertical blanking interval of the television signal, but data may be placed elsewhere in the signal and the invention is not limited in this respect. For example, data could be amplitude modulated on a sound carrier as is well known. As herein described, in-band transmission means the transmission of data within the video television channel comprising both audio and video carriers. Thus, the data from ISP 142 may be transmitted by amplitude modulation on the sound carrier, hereinafter in-band audio data, or in the vertical or horizontal blanking periods of an analog television signal, hereinafter in-band video data. ISP 142 may also be arranged to supply the data for transmission during unused portions a digital data stream such as an MPEG compressed video data stream.

-20-

ISP 142 can also receive and/or generate information locally. For example, ISP 142 may generate messages for transmission to subscribers concerning upcoming events or service interruptions or changes. If received from an information service provider, the information may either be transmitted as received or be reformatted by ISP 142, then supplied to scrambler 130
5 for transmission to subscribers.

ISP 142 also passes information to a head-end controller ("HEC") 132, which is connected to scrambler 130 and an out-of-band transmitter 134. Although HEC 132 is illustrated as being connected to the same scrambler as ISP 142, HEC 132 may in fact be connected to a different scrambler or scramblers. HEC 132 may conveniently be a Scientific-Atlanta Model
10 8658 for controlling transmission of data to scrambler 130 and out-of-band transmitter 134. As noted above, scrambler 130 places data in-band for transmission to subscribers, along with scrambling an associated television signal. Out-of-band transmitter 134 transmits information on a separate carrier, i.e., not within a channel. In one implementation, the out-of-band carrier is at 108.2 MHz, but other out-of-band carriers may also be used. The information transmitted
15 under the control of HEC 132 may, for example, be descrambling data. In one arrangement, information is inserted in each vertical blanking interval to indicate the type of scrambling employed in the next video field. Scrambling systems are well known in the art. For example, sync suppression scrambling, video inversion scrambling, and the like, or some combination of scrambling techniques may be used. Further, authorization information can be transmitted.
20 Authorization information authorizes subscribers to receive certain channels or programs. Information from ISP 142 and/or HEC 132 may also be transmitted over non-scrambled channels

-21-

via data repeaters (not shown) such as a Scientific-Atlanta Model 8556-100 data repeater as either in-band audio or video data.

Some of the transmitted information is global, i.e., it is transmitted to every subscriber. For example, the descrambling data may be a global transmission. It is noted that just because
5 each subscriber receives the descrambling data does not mean that each subscriber terminal unit can descramble a received signal. Rather, only authorized subscriber terminal units are capable of descrambling the received signal. On the other hand, some information transmissions may be addressed transmissions. For example, authorization information would normally be addressed to individual subscribers. That is, when transmitted, the data will have an address
10 (for example, a subscriber terminal unit serial number) associated with it. The addressed subscriber terminal unit receives the information and responds accordingly. Other subscriber terminal units will ignore the data. Further, there can be group addressed data, which will affect groups of subscriber terminal units.

The outputs of modulators 128-1, 128-2, any additional modulators, and out-of-band
15 transmitter 134 are supplied to a combiner 136 that combines the individual channels into a single wide-band signal that is then transmitted via distribution network 138 to a plurality of subscriber locations 120-1, ..., 120-n (see Figure 2C). Distribution network 138 may include, for example, one or more optical transmitters 140, one or more optical receivers 142, and a coaxial cable 144.

20 As indicated in Figure 2B, subscription television system 100 may include a plurality of head-end installations which each provide information to locations in a particular city or

-22-

geographic region. A central control 146 may be provided to coordinate the operation of various head-end installations in subscription television system 100. Central control 146 is often associated with the central office of a multi-service operator and may communicate with and control head-end installations in many cities. Central control 146 includes a system control
5 computer 148 that directs the other components of central control 146. One example of a system control computer 148 is a Scientific-Atlanta System Manager 10 network controller. Central control 146 may, for example, provide billing services for the service provider, including billing for pay-per-view events. A billing computer 150 stores billing data and may also format and print bills. Communication between system control computer 148 and HEC 132 may be via
10 modem, although the invention is not limited in this respect. Authorization data may be transmitted from system control computer 148 to HEC 132. HEC then 132 appropriately formats the authorization data and transmits the formatted authorization data to subscriber terminal units either in-band through scrambler 130 or out-of-band through out-of-band data transmitter 134 as discussed above.

15 Head-end installation 125 also includes an RF processor 152 for receiving reverse path data communications from subscriber locations 120-1, ..., 120-n. These data communications may include billing information for impulse-pay-per-view purchases which may be forwarded to system control computer 148 and may also include subscriber requests for database information maintained at head-end installation 125. For example, a database server 154 such
20 as an Oracle ® database server may provide access to reference materials such as encyclopedias, atlases, dictionaries, and the like. The subscriber request is forwarded from RF processor 152

-23-

to an information request processor 156 which accesses database 154 for the requested information and forwards the requested information to the requesting subscriber, for example, via an addressed in-band or out-of-band transaction as described above. In addition, information request processor 156 may also access a communications network 158 in order to provide
5 subscriber access to services such as the Internet.

As the amount of the data transmitted between the head-end installation and the subscriber locations increases, increased use will likely be made of out-of-band and digital transmission. For example, 50 MHz of bandwidth may be dedicated to digital data (non-video) transmission, both forward channel (to the subscriber terminal unit) and reverse channel (from
10 the subscriber terminal unit). 200 MHz or more may also be allocated to digital video and 300 MHz to 500 MHz may be allocated for analog video. Accordingly, although various illustrative transmission techniques are discussed above, the present invention is not limited in any respect by the manner in which information is communicated between the head-end installation and the subscriber locations.

Referring to Figure 2C, each subscriber location 120-1, ..., 120-n includes a subscriber terminal unit 160 connected to distribution network 138. "Subscriber location" as used herein refers to any location which is remotely located with respect to head-end installation 125. In accordance with the instant invention, a subscriber terminal may, for example, be located in a home, a classroom, a hotel room, a hospital room, or an office. Each subscriber terminal unit
15 160 may be coupled to one or more devices 162-1, ..., 162-n. Devices 162-1, ..., 162-n may include devices which are capable of being operated in response to user-supplied commands and
20

-24-

the instant invention is not limited in this respect. Thus, the devices may include televisions, stereo receivers, video cassette recorders (VCRs), audio cassette recorders, compact disc (CD) players, video disc players, video game players, computers, and the like. Certain ones of the devices may be operatively connected together. Thus, as shown in Figure 2C, device 162-1 is
5 connected to device 162-2. For example, device 162-2 may be a television and device 162-1 may be a video cassette recorder. For purposes of discussion, it will be assumed that device 162-1 is a video cassette recorder and that device 162-2 is a television. One or more of devices 162-1, ..., 162-n may be connected to switched power outlets of subscriber terminal unit 160, whereby subscriber terminal unit 160 may internally effect the on and off switching of these
10 devices. A remote control unit 166 communicates information to subscriber terminal unit 160 over a communication link 168. Communication link 168 may, for example, be an infrared link.

Figure 3 is a detailed block diagram of subscriber terminal unit 160. The wide-band signal from communications network 138 is supplied to an analog tuner 170, a data receiver 198, and a digital tuner 202. Analog tuner 170 and digital tuner 202 are tunable according to a
15 channel selected by a subscriber. Analog tuner 170 is tunable, for example, over a frequency range of 54 MHz to 550 MHz and can be tuned to a predetermined "off-channel" for receiving in-band data when television 160-2 is switched off. This so-called off-channel may be predetermined by system control computer 148 (see Figure 2B) and data identifying the predetermined channel may be forwarded to subscriber terminal unit 160 using any one of the
20 data transmission techniques described above. The off-channel identification data may be stored

-25-

in memory of subscriber terminal unit 160. Preferably, only one of the analog and digital tuners is active at a given time.

Analog tuner 170 uses a phase-locked loop under the control of analog control circuit 172 to convert the selected or predetermined off channel signal to a 45.75 MHz intermediate frequency (IF) signal. Analog control circuit 172 may, for example, be an application specific integrated circuit (ASIC) which combines a plurality of subscriber terminal unit control and data handling functions into a single unit. Of course, the ASIC may include any combination of individual control circuits. Alternatively, or in addition, other control circuitry may be used, such as a microprocessor. Analog control circuit 172 has an associated RAM 196 and ROM 197.

A filter 174, for example, a SAW filter, filters the IF signal from analog tuner 170 to split the signal into separate video and audio portions for processing. The video portion is demodulated and descrambled by video demodulator and descrambler 176 under the control of analog control circuit 172. For example, if sync suppression scrambling has been used, video demodulator and descrambler 176 may perform sync restoration. The video signal then passes through a bandpass filter 178 to an on-screen display control 180 where inverse video inversion (descrambling) takes place, if necessary. The descrambling of the video portion, whether sync suppression, sync inversion, video line inversion, and the like, is under the control of analog control circuit 172. Thus, analog control circuit 172 supplies to on-screen display control 180 any necessary timing signals, inversion axis levels, and information about whether the video is inverted and supplies to video demodulator and descrambler 176 any necessary timing,

-26-

restoration levels, and identification of sync pulses to be restored. Analog control circuit 172 receives the descrambling data for implementing such control, for example, from pulses as in-band audio data or from data modulated on the video during the vertical blanking interval.

In the other path, the audio signal is converted to the intermodulation frequency of 4.5
5 MHz by a synchronous detector 182. Feedback for automatic gain control of synchronous detector 182 is supplied from the output of a bandpass filter 184. An amplitude modulation detector 186 performs pulse detection to recover in-band audio data which is amplitude modulated onto the audio carrier. The detected in-band audio data is supplied to analog control circuit 172. The in-band audio data, except for descrambling data, is stored in RAM 196 for
10 buffering. The descrambling data is directly accessed by analog control circuit 172 for the above-described descrambling operations. The audio signal from bandpass filter 184 is demodulated by an FM demodulator 188. Volume control of the audio signal is performed under control of a volume control circuit 190 and a main processor 200 as described, for example, in commonly assigned U.S. Patent No. 5,054,071, which is incorporated herein by
15 reference. After volume control, the audio signal is supplied to a mute switch 192 which is under the control of main processor 200. The output of mute switch 192 is supplied to a modulator 194.

The output of on-screen display control 180 is supplied to analog control circuit 172 for detecting in-band video data from the blanking intervals of the signal. Analog control circuit
20 172 stores the detected data in RAM 196 prior to processing by main processor 200. As noted above, any descrambling data is directly accessed by analog control circuit 172 for the above-

-27-

described descrambling operations. Additional details of the detecting of this in-band video data can be found in commonly assigned copending application Serial No. 08/229,805, filed April 19, 1994, entitled "Subscription Television System and Terminal for Enabling Simultaneous Display of Multiple Services", which is incorporated herein by reference. Further, time-of-day data is transmitted from head-end installation 125 and stored in RAM 196, for example. For example, global time-of-day transmissions may periodically occur, based on satellite time standards as described in commonly assigned U.S. Patent No. 4,994,908, which is incorporated herein by reference. Thus, main processor 200 has access to current time-of-day information.

On-screen display control 180 selectively generates on-screen character and graphics displays in place of or overlaid on the video signal. For example, information stored in RAM 196 or ROM 197 may be read out to on-screen display control 180 and used to generate on-screen characters and/or graphics. Modulator 194 combines the output of on-screen display control 180 and the audio signal from the output of mute switch 192 and converts the combined signal to the channel frequency selected by main processor 200, such as channel 3 or 4. The combined and remodulated signal is supplied as an RF output to VCR 162-1 and/or to television 162-2 in a well known manner.

The input wide-band signal is also supplied to out-of-band data receiver 198. Out-of-band data receiver 198 provides received out-of-band data to analog control circuit 172. This data may be stored in RAM 196 where it is accessible by main processor 200.

The input wide-band signal is also supplied to a digital tuner/demodulator 202 which is tunable in a range, for example, from 400 MHz to 750 MHz and is tuned in accordance with

-28-

a subscriber selection. Digital tuner/demodulator 202 is used to tune to digital data channels. A digital control circuit 204 which may include an ASIC recovers and processes the digital data on the tuned digital data channel and supplies corresponding analog and/or digital output signals to one of devices 162-1, ..., 162-n. Alternatively, the recovered digital data may be accessed
5 by one of devices 162-1, ..., 162-n. For example, if the digital data includes digital audio data, corresponding analog output signals may be supplied to speakers. If the digital data is video game data, a video game player may access the recovered digital data which is stored in RAM 206, for example, through a video game player port (not shown). If the digital data includes digital television data, corresponding analog output signals may be supplied to VCR 162-1
10 and/or to television 162-2. If the digital data includes software programs, a personal computer may access the recovered software programs through a serial port. Details of digital control circuits which may be used to recover and process digital data may be found, for example, in commonly assigned U.S. Patent No. 5,239,540 to Rovira; commonly assigned U.S. Application Serial No. 08/352,162, entitled "Secure Authorization and Control Method and Apparatus for
15 a Game Delivery Service"; and commonly assigned U.S. Application Serial No. 07/970,918, entitled "System and Method for Multiplexing a Plurality of Digital Program Services for Transmission to Remote Locations." Each of these patents or applications is incorporated herein by reference thereto. Digital control circuit 204 also has an associated ROM 208.

Although digital tuner 202, digital control circuit 204, RAM 206, and ROM 208 are
20 shown as being integral with the remaining circuitry, these elements may alternatively be

-29-

provided as an add-on unit which is connectable to main processor 200 via an expansion slot connected to processor bus 224.

Subscriber terminal unit 160 further includes an LED display 210 for displaying information such as channel numbers, a keypad 212 for inputting subscriber commands, an infrared receiver 214 for receiving commands from remote control 166, and a VCR control 216 for transmitting commands to VCR 162-1 by, for example, IR signals. An RF transmitter is controllable by main processor 200 for transmitting reverse path transmissions over distribution network 138. These transmissions may be generated in response to subscriber-supplied inputs for requesting information from database 154 at head-end installation 125 or for the purpose of transmitting billing information regarding impulse pay-per-view purchases to system control computer 148. A switched power outlet 226 may be provided to selectively power one or more of devices 162-1, ..., 162-n plugged therein.

Main processor 200 is preferably a PowerPC[®] microprocessor and controls the overall operation of subscriber terminal unit 160 in accordance with program code stored in memory (e.g., ROM 218 and RAM 220) and with data downloaded from head-end installation 125.

In accordance with the instant invention, head-end installation 125 transmits vocabulary data representative of a vocabulary of spoken sounds or words to subscriber terminal units 160. This vocabulary provides, for example, for spoken control of devices 162-1, ..., 162-n and for spoken control of access to information transmitted by head-end installation 125. Specifically, the transmitted vocabulary may allow a user to use spoken commands to navigate viewing guides and other electronic programming guide menus as well as change channels, control a VCR if

-30-

present, adjust volume, and power his or her television on and off. The vocabulary data may be either phoneme data or template data and may be provided by one or more of information providers 114-1, ..., 114-n or may be generated at head-end installation 125 by, for example, ISP 142 as will be discussed below. Main processor 200 of subscriber terminal unit 160
5 executes a speech recognition algorithm using the vocabulary data transmitted from head-end installation 125 to recognize utterances spoken by a user. One particularly suitable speech recognition algorithm is VProFlex available from VPC. Other suitable speech recognition algorithms are available from IBM, Lernout & Hauspie, Verbex, and Dragon. Recognized utterances may include commands used to control devices 162-1, ..., 162-n and/or to access
10 information distributed by head-end installation 125.

Various hardware arrangements may be utilized to implement the speech recognition interface. In a first illustrative arrangement shown in Figure 4, remote control 166 includes a conventional wireless microphone 598 and a transmitter 599 for transmitting the spoken sounds or words to subscriber terminal unit 160 using RF transmission. Subscriber terminal unit 160
15 includes an RF receiver 301, an analog front end 302 for conditioning the received signal, a codec 303 for performing an analog-to-digital conversion of the conditioned signal, and an interface circuit 304 for interfacing to main processor bus 224. Subscriber terminal unit 160 also includes a ROM 305 for storing the speech recognition software and phoneme definitions, a RAM 306 for storing vocabulary and for serving as a scratch pad, and an optional flash
20 memory 307 for storing vocabulary if it is desired to maintain the vocabulary after power is removed. Flash memory 307 may also store program code to provide the capability of changing

-31-

programs. It is noted that ROM 305, RAM 306, and flash memory 307 are being used by main processor 200 to perform the speech recognition operation and that if adequate memory is available within the baseline memory of subscriber terminal unit 160, ROM 305, RAM 306, and flash memory 307 need not be provided.

5 Main processor 200 performs the speech recognition operation of the sounds or words spoken by the user by accessing the speech recognition software stored in ROM 305 and the vocabulary stored in RAM 306 and/or flash memory 307 via interface circuit 304. Specifically, RAM 306 and/or flash memory 307 stores phonemic or template vocabulary data downloaded from head-end installation 125. For example, when the sounds or words are a spoken command
10 for controlling VCR 162-1 or television 162-2, main processor 200 uses the phonemic definitions and speech recognition software of ROM 305 to compare the sounds or words spoken by the user with the phonemic or template vocabulary data stored in RAM 306 and/or flash memory 307 to recognize the spoken command. Main processor 200 then either executes the recognized command internally (such as powering the television on and off or a tuning the television to a
15 selected channel) or forwards the command to the appropriate device for execution. As a power-saving feature, a threshold element 310 may be provided to sense when the sound level exceeds a certain level and enable interface 304 and other components only when sound which is potentially recognizable speech exists.

A second illustrative arrangement of the speech recognition interface is shown in Figure
20 5. In this second arrangement, remote control 166 includes a microphone 320, an analog receiver 322 for conditioning the sound signal from microphone 320, a codec 324 for performing

-32-

an analog-to-digital conversion of the conditioned signal, and a transmitter 326 for transmitting the digitized sound data signal to subscriber terminal unit 160 using, for example, infrared or radio frequency signals. The digitized data requires a data transfer rate of at least 64k bits per second. Subscriber terminal unit 160 includes a receiver 328 for receiving the digitized sound data signal and an interface circuit 330 for interfacing to main processor bus 224. It is noted that if the digitized sound data signal is transmitted using infrared signals, infrared receiver 214 of subscriber terminal unit 160 may be used to receive the digitized sound data signal. Subscriber terminal unit 160 also includes a ROM 332 for storing the speech recognition software and phoneme definitions, a RAM 334 for storing vocabulary and for serving as a scratch pad, and an optional flash memory 336 for storing vocabulary if it is desired to maintain the vocabulary after power is removed. Flash memory 336 may also store program code to provide the capability of changing programs. Main processor 200 uses the phonemic definitions and speech recognition software of ROM 332 to compare the received digitized sound data signal with the phonemic or template vocabulary data stored in RAM 334 and/or flash memory 336 to recognize the spoken utterances. As a power-saving feature, a threshold element (not shown) may be provided to sense when the sound level exceeds a certain level and to enable interface circuit 330 and other components only when sound which is potentially recognizable speech exists. A similar threshold element (not shown) may also be provided in remote control 166, if desired.

A third illustrative arrangement of the speech recognition interface is shown in Figure 6. The arrangement of Figure 6 is the same that of Figure 5 except that remote control 166

-33-

further includes a digital signal processor 340. Digital signal processor 340 analyzes the digitized sound signal from codec 324 to extract spectral data. Transmitter 326 transmits the extracted spectral data to subscriber terminal unit 160. Because spectral data is transferred rather than digitized sound data, the data transfer rate is much lower than that of the arrangement of Figure 5, i.e., less than 10 k bits per second. This data transfer rate is better suited for infrared transmission between remote control 166 and subscriber terminal unit 160. As noted with respect to Figure 5, infrared receiver 214 of subscriber terminal unit 160 may be used to receive the transmitted spectral data if infrared transmission is used. Because the spectral analysis of the sound is performed in remote control 166, the loading of main processor 200 during the speech recognition operation is 30 to 50% less than in the Figure 5 arrangement.

It is noted that the remote controls of the first, second, and third arrangements include appropriate circuitry such as a keypad (not shown) for inputting and supplying conventional tuning, volume, etc. commands to subscriber terminal unit 160. The conventional circuitry may use transmitters 326 and 599 to transmit these conventional commands or separate transmitters may be used.

A fourth illustrative arrangement of the speech recognition interface is shown in Figure 7. In this arrangement, remote control 166 does not perform any speech-related functions. Thus, subscriber terminal unit 160 is directly connected to a microphone 352 which may have a cone surround or use an array of multiple microphones to improve signal to noise ratio. Subscriber terminal unit 160 also includes an analog front end 354 to condition the sound from microphone 352, a codec 356 for performing an analog-to-digital conversion of the conditioned

-34-

signal, and an interface circuit 358 for interfacing to main processor bus 224. A ROM 357 stores the speech recognition software and phoneme definitions, a RAM 359 stores vocabulary and serves as a scratch pad, and an optional flash memory 360 stores vocabulary if it is desired to maintain the vocabulary after power is removed. Flash memory 360 may also store program code to provide the capability of changing programs.

A fifth illustrative arrangement of the speech recognition hardware is shown in Figure 8. This fifth arrangement is the same as the arrangement shown in Figure 7, except that a digital signal processor 362 is provided to extract spectral data from the digitized output of codec 356. The inclusion of digital signal processor 362 serves to reduce loading on processor 200 during the speech recognition operation as compared with the arrangement of Figure 7.

Several optional features may be applied to each of the above-identified arrangements. First, on those remote controls which perform speech-related functions, a press to speak (or <Recognize>) button may be used to exclude spurious noise and/or to extend battery life. Thus, the speech-related circuitry may be powered only when the press to speak button is pressed. Second, in those arrangements where the speech-related functions are provided in subscriber terminal unit 160, a "wake-up" speech command may be used and other command recognition inhibited until the wake-up is recognized. For example, the system might wait for the word "ATTENTION", and then recognize additional utterances for 30 seconds. In addition, various mechanisms may be employed to reduce extraneous sounds. For example, a second microphone may be included on the speech input device which samples the ambient noise and subtracts it from the spoken signal. Alternatively, any television audio which is received at the

-35-

microphone may be removed by subtracting from the microphone input data the known television audio signal which is being generated by the subscriber terminal unit. This would assist in preventing recognition of "commands" or "utterances" spoken by television voices.

Figure 9 is an illustration of a remote control 166. Remote control 166 includes a
5 numeric keypad 751 including number buttons <0>, <1>, ... <9>; VCR control buttons 752 including <Rewind> button 753, <Play> button 754, <Fast Forward> button 755, <Pause> button 756, <Stop> button 757, and <Record> button 758; <Volume> control button 762; <Channel> control button 763; <Mute> button 764; <Last> channel button 765; <Electronic Program Guide> button 766; <Select> button 767; <Menu> button 768;
10 <Information> button 769; <Power> button 770; cursor control 771; and <Recognize> button 772. <Recognize> button 772 is provided so that the user may activate the speech recognition interface of the instant invention by supplying power to the speech-related components of remote control 166. In this regard, it is noted that the arrangements of Figures 7 and 8 do not include any speech-related components in remote control 166. Accordingly,
15 remote controls used in these respective arrangements would not include a <Recognize> button. In the arrangements of Figures 7 and 8, an "ATTENTION" command would be spoken by the user in order to activate the speech recognition interface in subscriber terminal unit 160. The remainder of the keys and buttons on remote control 166 operate in a conventional manner and will not be discussed in detail herein.

20 Head-end installation 125 may be configured to transmit different vocabulary data to different subscriber terminal units. For example, vocabulary data may be provided to subscriber

-36-

terminal units in accordance with a monthly service fee. Thus, for a first service fee, first vocabulary data for defining commands to implement basic spoken controls of a device such a television may be provided to a subscriber terminal unit. For a second higher service fee, second, more sophisticated vocabulary data for implementing extended spoken controls of the television, as well as control of a VCR, stereo, game player, etc. may be provided to a subscriber terminal unit. The second vocabulary data may also define words and commands which may be used to access information transmitted by head-end installation 125. Higher services fees may also be charged for the actual accessing of the information which is controlled by the more sophisticated speech interface.

10 When a display is provided which includes text which may be spoken as a command or a recognized word, such commands or recognized words are preferably highlighted in some manner, such as by coloring them green in a manner similar to that in which keywords are highlighted in the Microsoft® Windows® Help features, in order to cue the user.

15 Exemplary downloaded vocabularies will be discussed below. For the purposes of these discussions, it will be assumed that the vocabulary data is phonemic data. It is noted that use of phonemic data and the specific commands in each of the vocabularies are for illustrative purposes only and the invention is not limited in these respects.

20 A first vocabulary for permitting spoken control of a television will now be described. The first command vocabulary may be provided to permit a user to perform basic television controls such as (1) ON/OFF power control using "POWER ON" and "POWER OFF" commands; (2) volume control using "VOLUME NUMBER", "VOLUME UP", and "VOLUME

-37-

DOWN" commands; and (3) channel selection control using "GOTO CHANNEL *NUMBER*", "SURF UP", "SURF DOWN", "LAST" channel commands. The phonemic vocabulary data representing the first vocabulary may be transmitted, for example, by an addressed transmission in accordance with any of the above-described data transmission techniques to subscribers who have paid a first predetermined service fee. The phonemic vocabulary data representing the first vocabulary may be generated by ISP 142 using a commercially available text-to-speech/phoneme translation program or may be provided to ISP 142 from one of the information providers. The phonemic data may likewise be generated by the information providers using a text-to-speech/phoneme translation program. The basic television controls mentioned above may be implemented by an illustrative, but non-limiting, first vocabulary set forth in Table I.

TABLE I

Power	One	Two	Three	Four
Five	Six	Seven	Eight	Nine
Ten	Eleven	Twelve	Thirteen	Zero
O	Fifteen	Teen	Thirty	Forty
Fifty	Sixty	Seventy	Eighty	Ninety
Twenty	Hundred	Up	Down	Channel
Off	Surf	Power	Stop	On
Last	Attention	Goto		

A command grammar which specifies how the words of the first vocabulary may be used may also be transmitted. Thus, for example, the commands "POWER ON" and "POWER OFF" are allowable commands, but "ON POWER" and "OFF POWER" may be excluded. The command grammar may also include context specific rules. For example, the "POWER ON" command may be allowed only when the television is OFF. As noted above, some or all of the

-38-

command grammar and context-specific rules may be permanently resident in the memory of the subscriber terminal unit.

The control of television 162-2 using the command vocabulary of Table I will now be explained. In general terms, when a <Recognize> button 772 is present on remote control 166, the recognition operation of the instant invention is activated by pressing the <Recognize> button 772. When no <Recognize> button is present on remote control 166, the recognition operation is activated by speaking an activation command such as "ATTENTION". When activated, subscriber terminal unit 160 preferably provides a suitable indication to this effect to the user. For example, main processor 200 and on-screen display control 180 may superimpose a display of the word "Listening ..." in the lower center of the screen of television 162-2 to provide the indication. It is noted that the indication of the activation of the speech recognition interface is not limited to an on-screen display and may, for example, be an aural indication in addition to or in place of the on-screen display. After the indication, the user may speak sounds or words for controlling television 162-2 in accordance with the command vocabulary. It is noted that the indication is provided to enhance the speech recognition user interface, but such an indication is not a required feature of this invention.

Main processor 200 uses the phonemic definitions and speech recognition software stored in memory as discussed above to compare the spoken sounds or words with the phonemic data of the vocabulary. If the comparison results in a recognition of a command, television 162-2 is appropriately controlled. If the comparison does not result in a recognition of the command, one or more of several actions occurs. An indication may simply be provided to the user that

-39-

the command was not recognized and the user may be prompted to repeat the command or to use the keypad to implement the command (if possible). If a command is repeated nonsensically, for example, "GOTO CHANNEL SIXTEEN" is repeated twice in a subscription television system in which channel sixteen is not a valid channel, subscriber terminal unit 160
5 may assume that a misrecognition occurred the first time and that the user actually wants to tune to a similar-sounding channel, probably channel 60. If the top two recognition options have comparable likelihoods, the user is informed what the two options are and is asked to select one over the other. If a user has frequently spoken a specific command, for example, "GOTO CHANNEL SIXTEEN" (ESPN perhaps) but has, in this case, apparently selected a less
10 frequently accessed command, such as "GOTO CHANNEL SIXTY" (PBS perhaps), the more commonly spoken command may be implemented. In addition, if the recognition algorithm includes a speaker identification algorithm which can recognize a specific speaker's voice, this adaptive learning of recognition preferences may be tailored to each speaker. In addition, based upon context, only specific commands may be valid. For example, if the television is turned
15 off, the only feasible command is "POWER ON", and a spoken command that resembles that phrase should be interpreted accordingly.

The steps for turning television 162-2 ON using the speech recognition interface will now be described. First, the user activates the speech recognition interface by pressing a <Recognize> button on a remote control or by saying "ATTENTION", as appropriate. The
20 user then says "POWER ON". If the "POWER ON" command is recognized, television 162-2 is switched ON and tuned to the last viewed channel. Preferably, the corresponding channel

-40-

number is displayed. Other information such as current time, channel identifiers such as CBS, ABC, NBC, and the like, may also be displayed.

The steps for turning television 162-2 OFF using the speech recognition interface will now be described. After activating the speech recognition interface, the user says "POWER
5 OFF". If the "POWER OFF" command is recognized, television 162-2 is turned OFF.

One technique for controlling the sound level using the speech recognition interface will now be described. After activating the speech recognition interface, the user says "VOLUME
10 *NUMBER*", where *NUMBER* is a number which specifies volume on a fixed scale, such as a linear scale from 1 to 10. If the "VOLUME *NUMBER*" command is recognized, a line bar such as shown in Figure 10 with the current volume level shaded in is displayed on the television screen. The volume level is then set to the volume level corresponding to the number *NUMBER* and the volume line bar is updated. The updated line bar preferably remains on the television screen for some predetermined period of time such as two seconds.

The user may also say "VOLUME UP" after activating the speech recognition interface.
15 If the "VOLUME UP" command is recognized, the television screen displays a line bar such as shown in Figure 10 with the current volume level shaded in. The sound level is then increased by one unit every two seconds until the user says "STOP". Preferably, the television screen displays a prompt such as "SAY STOP WHEN DESIRED VOLUME HAS BEEN REACHED."
20 When the user says "STOP", the volume level is tuned to the current increased level and the volume line bar is updated. The volume line bar remains on the screen for some predetermined period of time such as two seconds. It should be noted that if the user has a remote control with

-41-

a <Recognize> button, this button must be actuated when the user speaks the "STOP" command. If the spoken activation command is used, the speech recognition interface will be active for some predetermined time period after the activation command or the most recent command (i.e., "VOLUME UP") is spoken.

5 The user may also say "VOLUME DOWN" after activating the speech recognition interface. If the "VOLUME DOWN" command is recognized, the television screen displays a line bar such as shown in Figure 10 with the current volume level shaded in. The sound level is then decreased by one unit every two seconds until the user says "STOP". Preferably, the television screen displays a prompt which prompts the user to say "STOP" when the desired
10 volume has been reached. When the user says "STOP", the volume level is tuned to the current decreased level and the volume line bar is updated. The volume line bar remains on the screen for some predetermined period of time such as two seconds. Again, it should be noted that if the user has a remote control with a <Recognize> button, this button must be actuated when the user speaks the "STOP" command. If the spoken activation command is used, the speech
15 interface will be active for some predetermined time period after the activation command or the most recent command (i.e., "VOLUME DOWN") is spoken.

A direct channel tuning operation using the speech recognition interface will now be explained. After activating the speech recognition interface, the user says "GOTO CHANNEL
20 NUMBER", where *NUMBER* is a channel number. If the "GOTO CHANNEL *NUMBER*" command is recognized, the television screen displays the channel number *NUMBER* and the television is tuned to the channel corresponding to the spoken channel number *NUMBER*. If the

-42-

user has purchased an electronic programming guide option, the title and a short summary of the current programming on the tuned channel are also preferably displayed.

A first channel scanning ("surfing") operation using the speech recognition interface will now be explained. It will be assumed that the television is currently tuned to channel 2. After activating the speech recognition interface, the user says "SURF UP". Alternatively, of course, other descriptive vocabulary may be used in place of "SURF" such as "SCAN". If the "SURF UP" command is recognized, the television screen may display a prompt such as "RECOGNIZE SURF UP. SAY "STOP" WHEN DESIRED CHANNEL IS REACHED." Television 162-2 is then tuned to channel 3 and the television screen displays "3." Television 162-2 remains tuned to channel 3 for two seconds and is then tuned to channel 4, 5, etc. Each available channel is tuned to for two seconds and a display of the corresponding channel number is provided. If the user says "STOP" when, for example, channel 50 is the current channel, television 162-2 remains tuned to the current channel and the channel number display is provided for a predetermined period of time such as two seconds. It should be noted that if the user has a remote control with a < Recognize > button, this button must be actuated when the user speaks the "STOP" command. If the spoken activation command is used, the speech recognition interface will be active for some predetermined time period after the activation command or the most recent command (i.e., "SURF UP") is spoken.

A second channel scanning ("surfing") operation using the speech recognition interface will now be explained. It will be assumed that the television is currently tuned to channel 50. After activating the speech recognition interface, the user says "SURF DOWN". If the "SURF

-43-

DOWN" command is recognized, the television screen may display a prompt such as "RECOGNIZE SURF DOWN. SAY STOP WHEN DESIRED CHANNEL IS REACHED." Television 162-2 is then tuned to channel 49 and the television screen displays "49". Television 162-2 remains tuned to channel 49 for two seconds and is then tuned to channel 48, 47, etc. Each available channel is tuned to for two seconds and a display of the corresponding channel number is provided. If the user says "STOP" when, for example, channel 2 is the current channel, television 162-2 remains tuned to the current channel and the channel number display is provided for a predetermined period of time such as two seconds. It should be noted that if the user has a remote control with a <Recognize> button, this button must be actuated when the user speaks the "STOP" command. If the spoken activation command is used, the speech recognition interface will be active for some predetermined time period after the activation command or the most recent command (i.e., "SURF DOWN") is spoken.

A last or previous channel operation will now be explained. For purposes of this discussion, it is assumed that the television is currently tuned to channel 4. The user activates the speech recognition interface and says "GOTO CHANNEL TEN". If the direct channel tuning command is recognized, television 162-2 is tuned to channel 10 as discussed above with respect to the direct channel tuning operation. The user may then activate the speech recognition interface and say "LAST". If the "LAST" command is recognized, television 162-2 is tuned to the previously tuned channel, i.e., channel 4, and the corresponding channel number is displayed for a predetermined period of time. If the user activates the speech recognition interface and

-44-

says "LAST" again, television 162-2 is tuned to channel 10 and the corresponding channel number is displayed for a predetermined period of time.

If any of the above spoken commands is not recognized, any of the actions described above with respect to unrecognized commands may be implemented.

5 It is noted that each of the above-discussed commands is executed internally to subscriber terminal unit 160. That is, the powering on and off of television 162-2 is accomplished by appropriately controlling switched power outlet 226 into which television 162-2 is plugged. The television tuning and volume control operations are accomplished by appropriately controlling
10 tuners 170 and 204 and volume control circuit 190 and mute switch 192 of the subscriber terminal unit. However, the invention is not limited in this respect and recognized commands may be forwarded to one of devices 162 via infrared signals, for example, for execution.

Second vocabulary data for implementing control of VCR 162-1 and television 162-2 and for accessing electronic program guide (EPG) data will now be described. Accordingly, for purposes of the discussion below, it will be assumed that data signal 122-3 from information
15 provider 114-3 provides EPG data via satellite 123 to head-end installation 125 and that this data is transmitted as in-band data in the manner set forth above. Of course, the invention is not limited in this respect. The EPG data from information provider 114-3 includes television schedule information arranged by time and channel. One such information provider for providing EPG data is Insight Telecast Inc. System operators can purchase this data and provide
20 it to their subscribers.

-45-

The EPG information received at head-end installation 125 will often be very extensive, containing data for programs up to one or two weeks in advance. If all of this data is to be transmitted to subscriber terminal units 160, the subscriber terminal units must be able to store the EPG information in memory. To store EPG data for one or two weeks of programming requires a significant amount of memory. Providing extra memory in subscriber terminal units 160 is expensive because of the hundreds or thousands of such terminal units that are present in a typical information system. Frequently, subscribers may prefer a less expensive unit that provides only a portion of the EPG data supplied by the EPG information provider, such as the EPG data for next few hours. The subscribers can then benefit from lower cable service bills or purchase expenses if subscribers are to own the terminals. Thus, head-end installation 125 is preferably provided with the capability of selecting only certain portions of the EPG data to be transmitted to the subscriber terminal units. For example, ISP 142 may be provided with this capability. In addition, the downloaded vocabulary will be affected by the scope of the downloaded EPG information. For example, if the subscriber has selected a priced option which provides for title-addressable program selection (e.g., "FIND STAR TREK"), then the vocabulary data for the programming period selected (1 to 14 days) will be downloaded with the EPG data. In general, when the user selects a priced option such as messaging, an expanded channel line-up, wide area network access, or an expanded EPG, the corresponding grammar and vocabulary are also downloaded to subscriber terminal unit 160 from head-end installation 125. If the EPG data is received by ISP 142, ISP 142 selects the portion to be transmitted to subscribers and passes only that portion to scrambler 130. By selecting only a portion of the

-46-

data provided by the EPG information provider, less data is transmitted than would otherwise be the case. Thus, the data repetition rate is increased. ISP 142 may not only select portions of the EPG data, but may also add data on local stations not covered by information provider 114-3. ISP 142 may also reformat the data in such a way as to make it more pleasing to the subscribers.

If the EPG data is transmitted in the vertical blanking interval of at least one of the television signals, the EPG data is constantly transmitted in the vertical blanking interval by scrambler 130. Scrambler 130 has memory dedicated to storing the EPG data. The amount of memory depends on the amount of EPG data to be transmitted to the subscribers. If ISP 142 selects only a small portion of the EPG data provided by EPG information provider 114-3, e.g., the EPG data for a few hours, then a small memory, perhaps 128k bytes, may be sufficient. For larger segments, 512k bytes of memory may be necessary. For a couple of weeks of EPG data, 1M bytes of memory may be required. ISP 142 periodically updates the scrambler memory with new EPG data received from EPG information provider 114-3. ISP 142 tags the data as either long term or short term, depending on whether the data concerns a shortly upcoming program or a more distant one. The scrambler sends out the short term data more frequently than the long term data. This is because the EPG data is stored in memory at subscriber terminal unit 160, and must be updated frequently. But the subscriber terminal unit is not constantly tuned to the channel where the EPG data is located. Subscriber terminal unit 160 tunes to the EPG data channel (which may, for example, be the off-channel discussed above) whenever possible to obtain update information. By sending out short term data very frequently,

-47-

it is likely that a given subscriber terminal unit will have accurate short term data stored therein, which is the most important data to a user of the subscriber terminal unit. Long term data is sent out less frequently. Programming changes may also be grouped with the short term data. It will be appreciated that the EPG may be transmitted by other means and the invention is not
5 limited in this respect.

In order to provide spoken control of VCR 162-1 and television 162-2, as well as spoken access to EPG data transmitted from head-end installation 125, second vocabulary data may be downloaded from head-end installation 125. This second vocabulary data may be transmitted, for example, by an addressable transmission to subscribers who pay a second service fee which
10 is higher than the service fee for the first vocabulary. The second vocabulary permits the basic television controls described above, as well as control of VCR 162-2 and access to EPG data. More particularly, this second vocabulary permits a user to use spoken commands to implement basic television control, EPG control, VCR control, and event programming.

An electronic programming guide will be described generally so that a better
15 understanding of the instant invention may be obtained. With reference to Figure 11, horizontally indicated at block 60 are date and time slots. Channel selections appear vertically on the left side of the screen. Of course, the arrangement of the channels and times could be reversed in an alternative embodiment. For example, at block 62 is found HBO, which is channel 15 in Figure 11. The name of a television program is associated with each time slot and
20 channel slot. For example, associated with the 7:30 p.m. time slot and channel 14 is "Gilligans Island", shown at block 64. The channels on the left-hand side of the EPG are arranged in

-48-

numerical order from top to bottom. The EPG provides program descriptions which include the title, and may include other information such as ratings or an indication that the program is closed-captioned. For example, block 66 provides all of this information.

An illustrative, but non-limiting, vocabulary suitable for implementing this control includes the vocabulary of Table I above and the additional vocabulary of Table II below. Many of these words are prompted on the television screen as part of the EPG windowing. As noted above, on-screen text which may be spoken as a command or recognized word is preferably highlighted in some manner, such as by coloring it green in a manner similar to the Microsoft® Windows® Help features, in order to cue the user. The vocabulary below is a representative vocabulary and the user is prompted that a command or word of an on-screen display is a legal spoken command or word by highlighting the text in some suitable manner.

TABLE II

	Monday	Tuesday	Wednesday	Thursday	Friday
	Saturday	Sunday	AM	PM	VCR
15	Play	Record	Rewind	FastForward	Eject
	TV	Stereo	Clock	Left	Right
	Up	Down	One-Time	Daily	Weekly
	PreviousDay	NextDay	Select	Main-Menu	Guide
	EPG	Set	Change	Clear	Exit
20	More	Movies	Comedy	Messages	Program
	Goto	Page			
	Electronic-Programming-Guide		Pay-per-view		
	What's-on-cable		Favorite		
	Program-Timer		Parental-control		
25	Pending-Recordings		Cable-Terminal-Setup		
	Channel-Listing		Categories		
	Children-Education-Science		Drama-Romance		
	Entertainment-Variety		Sleep-timer		
	News-Talk-Magazine		Specials-Mini-Series		
30	Pre-Recorded Sports		Live-Sports		

-49-

Action-Mystery-Horror
Miscellaneous
Provide-Information-On

Viewing-Guide
Plus-Codes
Recordings

5 The general operation of the speech recognition interface using the second vocabulary is basically the same as with respect to the first vocabulary. That is, when a <Recognize> button is present on remote control 166, the speech recognition operation of the instant invention is activated by pressing the <Recognize> button. When no <Recognize> button is present on remote control 166, the speech recognition operation is activated by speaking an activation
10 command such as "ATTENTION". When activated, subscriber terminal unit 160 preferably provides a suitable indication to this effect to the user. For example, main processor 200 and on-screen display control 180 may superimpose a display of the word "Listening ..." in the lower center of the screen of television 162-2 to provide the indication. After the indication, the user may speak sounds or words for controlling the EPG, VCR 162-1 and television 162-2
15 in accordance with the second vocabulary. Main processor 200 uses the phonemic definitions and speech recognition software to compare the spoken sounds or words with the phonemic data of the second vocabulary. If the comparison results in a recognition of the command, VCR 162-1 or television 162-2 are appropriately controlled. If the comparison does not result in a recognition of the command, the actions described above for unrecognized commands may be
20 implemented.

 The basic television controls using the second vocabulary are the same as those described above and reference should be made thereto.

-50-

In accordance with the vocabulary set forth in Tables I and II and with reference to Figure 12, the use of the speech recognition interface to use the electronic program guide to determine "What's On Cable" will be described. After the speech recognition interface is activated, the user says "MAIN MENU." If the "MAIN MENU" command is recognized, the main EPG program menu listing shown in Figure 12A is displayed on the television screen and the user is prompted to make a selection. In general, the user may interact with the displayed listing using any or all of the following selecting techniques. First, the arrow keys on remote control 166 may be used to highlight one of the menu items. Second, an "UP" or "DOWN" command may be spoken to highlight one of the menu items. Third, the <Select> key on remote control 166 may be pressed to select the currently highlighted menu item. Fourth, a "SELECT" command may be spoken to select the currently highlighted menu item. Fifth, the numeric key <N> on remote control 166 may be pressed to select the N^{th} menu item. Sixth, a "SELECT N" command may be spoken to select the N^{th} menu item. Seventh, a "MENU ITEM NAME" command may be spoken to select the named menu item. Generally, the entire menu item name will be highlighted, indicating that it is available as a spoken command. For long menu item names, such as "Cable Terminal Setup", only a substring, for example, "Setup" may be highlighted to avoid long command phrases which may be inconvenient to speak (although they are easy to recognize). In this instance, the "Cable Terminal Setup" option may be selected by simply speaking "SETUP". The system may optionally be configured to recognize both the long command phrase and a substring for selecting a menu item. In addition, strings may be recognized which are close to, but do not exactly match a defined speech command. For

-51-

example, if the user says "INFO", but the valid corresponding command is "INFORMATION", the speech recognizer may correctly interpret the speech as a normal function of its matching capability.

If the user selects the "What's On Cable" menu item using any of the selecting techniques
5 described above and if the user is authorized to access the EPG, the "What's On Cable" menu shown in Figure 12B is displayed on the television screen and the user is prompted to make a selection.

If, when the "What's On Cable" menu of Figure 12B is displayed, the user selects the
"Viewing Guide" menu item using any of the selecting techniques identified above, the electronic
10 program guide of Figure 11 is displayed on the television screen. Because of the nature of a grid-style display, the instant invention provides a set of spoken navigation commands that may be used for large scale movement within a grid. Thus, when the EPG is displayed, a user may activate the speech recognition interface and say "GOTO CHANNEL *NUMBER*" to move to the row specified by the channel number *NUMBER* and may say "GOTO *TIME*" to move to the
15 column with the next occurrence of the specified *TIME*. The user may also speak "PAGE UP" and "PAGE DOWN" commands to page up and page down through the electronic programming guide. For finer navigation within a grid, the user may activate the recognition interface and speak the directional commands "MOVE UP", "MOVE DOWN", "MOVE LEFT", and "MOVE
20 RIGHT" as appropriate until a desired channel and program of the viewing guide of Figure 11 is highlighted. During this procedure, the television screen displays "Listening ..." and the cursor or highlighted area is moved appropriately within one second after the corresponding

-52-

directional commands are spoken. The user may also say "GOTO CHANNEL *NUMBER* AT *TIME*" and the highlighted area is then the row and column defined by the time *TIME* and channel number *NUMBER*.

5 Suppose the directional commands spoken by the user cause the viewing guide of Figure 11 to highlight 7:00 P.M. ESPN "Golf." If the user then says "INFO", the viewing guide menu of Figure 12C is then displayed and the user is prompted to make a selection. If the user selects the "Tune TV-To-Program" menu item using any of the selecting techniques described above and if the current time is during the selected program time, television 162-2 is tuned to the selected program.

10 If, when the viewing guide menu of Figure 12C is displayed, the user selects the "Record Program" menu item using any of the selecting techniques described above, the record program screen of Figure 12D is displayed. The record program screen of Figure 12D prompts the user to select one of the displayed record menu items, i.e., "One Time", "Daily", "Weekly" or "Exit" (to exit the record program routine). If the user selects "One Time" using any of the
15 selecting techniques described above, the confirmation screen of Figure 12E indicating the recording schedule is displayed. If VCR 162-1 is not on, the user may activate the speech recognition interface and say "VCR POWER ON". VCR 162-1 is then turned ON if it is not already ON. The system may then check to verify that a cassette has been loaded into VCR 162-1 and prompt the user to load a cassette into VCR 162-1 if none is present. The system
20 then appropriately records the selected program.

-53-

If, when the viewing guide menu of Figure 12C is displayed, the user selects the "Provide-Information-On Program" menu item, a program description is displayed on the television screen.

5 The use of the "Favorite Channel" feature of the EPG will be discussed. If, when the "What's On Cable" menu of Figure 12B is displayed, the user selects the "Favorite Channel" menu item using any of the selecting techniques described above and if the user has previously set up a favorite channels arrangement, the favorite channel guide of Figure 12F is displayed on the television screen. The favorite channel guide is a grid display that is a subset of the entire EPG grid display containing the user's favorite channels. This subset is user-specified and
10 can be as large as the full set of channels available, or as small as one channel. The user may then navigate and select from the favorite channel grid of Figure 12F as discussed above with respect to the EPG of Figure 11.

The "Channel Listings" feature of the EPG will be discussed. If, when the "What's On Cable" menu of Figure 12B is displayed, the user selects the "Channel Listings" menu item
15 using any of the selecting techniques described above, a channel listing of the available channels in the subscription television system such as shown in Figure 12G is displayed on the television screen. The user may then select one of these by speaking the "MOVE LEFT", "MOVE RIGHT", "MOVE UP", and "MOVE DOWN" commands and then saying "SELECT" or by saying "GOTO CHANNEL *NUMBER*." Selecting a channel will tune the television to that
20 channel.

-54-

The "Categories" feature of the EPG will now be discussed. If, when the "What's On Cable" menu of Figure 12B is displayed, the user selects the "Categories" menu item using any of the selecting techniques described above, the screen of Figure 12H is displayed. If, for example, the user selects the "Live Sports" menu item using any of the selecting techniques

5 described above, the current EPG database is searched. If the EPG database contains information that fits in the selected category, the screen of Figure 12I is displayed. If the user, for example, selects the "Baseball" menu item using any of the selecting techniques described above, the screen of Figure 12J is displayed. The user can then select one of these menu items to tune the television to that program. If the EPG database contains no information that fits in

10 the selected category, a message is displayed on the television screen which indicates that there are currently no programs in this category and the user is then prompted to return to the main menu of Figure 12A. It is noted that the display of programs matching the selected category may be limited to those programs either currently showing or starting within some relatively short, pre-defined time period.

15 The second vocabulary also permits control of the functions of VCR 162-1. VCR playback control will now be discussed. It is assumed that power has been turned on to subscriber terminal unit 160, VCR 162-1, and television 162-2 either using the speech recognition interface and/or the buttons of remote control 166 or keyboard 122 of subscriber terminal unit 160. A video cassette is inserted into the cassette compartment of VCR 162-1.

20 If the cassette has been properly loaded, a cassette icon, a "Cassette Loaded" message, and a prompt asking "Do You Wish To Play This Cassette Now?" are displayed on the television

-55-

screen. If the user activates the speech recognition interface and says "OK", television 162-2 is tuned to channel 3 or channel 4 in accordance with the manufacturing code and the tape begins to play.

Control of the VCR fast-forward and rewind operations using the speech recognition interface will now be discussed. It is assumed that subscriber terminal unit 160, VCR 162-1, and television 162-2 are turned ON, that the cassette has been properly installed, and that the television has been tuned to channel 3 or channel 4, as appropriate. If a tape is currently playing and the user activates the speech recognition interface and says "VCR FASTFORWARD" or "VCR REWIND", subscriber terminal unit 160 sends a signal such as an IR signal via IR transmitter 216 to VCR 162-1 which results in the tape moving forward or backward. The user may then say "VCR STOP" or press the <Stop> key on remote control 166 and the tape stops playing. If the user then says "VCR FASTFORWARD" or "VCR REWIND", the tape is fastforwarded or rewound and television 162-2 is tuned to the last tuned channel. If the user does not say "VCR STOP" or press the <Stop> button on remote control 166, the tape will advance or be rewound all the way to the end. It should be noted that if the user has a remote control with a <Recognize> button, this button must be actuated when the user speaks commands subsequent to the first spoken command. If the spoken activation command is used, the speech recognition interface will be active for some predetermined time period after the activation command or the most recent command is spoken.

Control of the VCR pause and continue functions will now be discussed. Assuming that a tape is currently playing, if the user activates the speech recognition interface and says "VCR

-56-

PAUSE", the subscriber terminal unit sends a signal such as IR signal via IR transmitter 216 to VCR 162-1 which causes the tape to be stopped and the tape counter to be displayed on the screen. If the user then says "VCR CONTINUE", the system sends a signal such as an IR signal via IR transmitter 216 which causes the tape to begin to play again. It should be noted
5 that if the user has a remote control with a <Recognize> button, this button must be actuated when the user speaks the "VCR CONTINUE" command. If the spoken activation command is used, the speech recognition interface will be active for some predetermined time period after the activation command or the most recent command (i.e., "VCR PAUSE") is spoken.

The setting of a VCR to record a program using the speech recognition interface will now
10 be discussed. It is noted that this discussion of VCR programming is based on a vocabulary which does not support program title commands, e.g., "RECORD STAR TREK." Other, simpler VCR programming methods are available with the more sophisticated vocabularies discussed below. For the purposes of this example, it is assumed that a user desires to record a TV program in SP mode on channel 7 in the first program position starting at 9:05 PM and
15 stopping at 10:35 PM on Saturday, December 17, 1994 and that the present time is 1:05 PM on Thursday, December 15, 1994. Starting at the main menu of Figure 12A, the user selects the "VCR-Program-Timer" menu item using any of the selecting techniques described above and the screen of Figure 12K is displayed. If the user selects the "Use PLUS Codes" menu item using any of the selecting techniques described above, the screen of Figure 12L is displayed. The user
20 then states the appropriate VCR Plus (TM) code one digit at a time.

-57-

Returning the screen of Figure 12K, if the user selects the "Set-Program-Timer" menu item using any of the selecting techniques described above, the screen of Figure 12M is displayed. If the user then selects the "EPG Program VCR" menu item, the screen of Figure 12B is displayed and VCR 162-1 may be programmed in accordance with the steps described above. If the user selects the "Voice Program VCR" menu item, the screen of Figure 12N is displayed and the user is prompted to select a program number. If the user selects menu item (1), the screen of Figure 12O is displayed and the user is prompted to state the day on which the program to be recorded is on. In accordance with the example set forth above, the user says "SATURDAY." In an alternative embodiment, a user could also say "DECEMBER SEVENTEENTH." This causes the screen of Figure 12P to be displayed and the user is prompted to state the start hour, the start minute, and either AM Or PM. The user then says "NINE O FIVE PM". The screen of Figure 12Q is then displayed and the user is prompted to state the stop hour, the stop minute, and either AM Or PM. The user then says "TEN THIRTY FIVE PM". The screen of Figure 12R is then displayed and the user is prompted to state the channel that the program is on. The user then says "SEVEN". The screen of Figure 12S is then displayed and the user is prompted to select the appropriate tape speed. After selecting the "SP" menu item in accordance with any of the selecting techniques described above, the screen of Figure 12T is displayed. The screen of Figure 12T prompts the user to verify that the entered information is correct. If the user says "OK", the screen of Figure 12U is displayed for a predetermined period of time and the user is subsequently returned to the main menu of Figure 12A.

-58-

Additional vocabulary data may be downloaded from head-end installation 125 to permit a user to speak commands using channel identifiers (e.g., CBS, NBC, ESPN, etc.) in addition to channel numbers. This additional vocabulary may be transmitted, for example, by an addressable transmission to subscribers who pay an additional service fee. An exemplary, but

5 non-limiting example, of vocabulary suitable for this feature is set forth in Table III below.

TABLE III

	Family	Channel	HBO1	HBO2	HOT
	International	ITV	Lifetime	Mainstreet	Cinemax
	Disney	Court	MEU	MTV	Playboy
10	Nickelodeon	EPG	Prime	QVC	Rainbow
	Request	Showtime	Shopping	Sneak	Spice
	Hundred	Black	Classifieds	Trinity	Travel
	TBN	TBS	The	Learning	Movie
	Nashville	Network	TNN	Nostalgia	USA
15	VH1	PPV	Vision	Weather	A&E
	Arts	American	AMC	BRAVO	Cartoon
	CMTV	CNN	CNBC	Comedy	CSPAN
	Discovery	E	Entertainment	ESPN	CBS
	NBC	FOX	PBS	ABC	IND
20	Pay	WPIX	WGN	WWOR	Atlanta
	Hits	Congress	Sports	Encore	

It will be appreciated that this vocabulary will include identifiers for local stations in a particular system and that the vocabulary may be periodically updated to take into account changes in the

25 offerings of a particular system.

In accordance with this additional vocabulary, the user may interface with the "What's on Cable" set of functions by proceeding directly to the network of choice using channel identifiers. Using this additional vocabulary, a user may use "GOTO CHANNEL IDENTIFIER" commands in addition to the "GOTO CHANNEL NUMBER" command discussed above. For

-59-

example, a user may navigate the electronic programming guide of Figure 11 by saying "GOTO ESPN" to move to the row specified by ESPN.

In accordance with an arrangement using a third vocabulary, EPG information provider 114-3 provides both EPG data and phonemic or template data corresponding to the EPG data to head-end installation 125. For purposes of the discussion below, it will be assumed that phonemic data corresponding to the EPG data is provided. Information provider 114-3 may, for example, use a text-to-speech/phoneme translator to generate the corresponding phonemic data. The EPG text data generally contains at least program title and description or description keyword data. Thus, EPG information provider 114-3 provides the program title and description data as well as phonemic data representing the spoken sounds or words constituting this program title and description or description keyword data. This phonemic data will hereinafter be referred to as "phonemic EPG data." ISP 42 thus receives the EPG data and the phonemic EPG data and transmits both the EPG and the phonemic EPG data to the subscriber terminal units of subscribers. Alternatively, ISP 42 may internally generate the phonemic EPG data using a text-to-speech converter for converting the received program title and description or description keyword data to phonemic data. In yet another variation, the phonemic data may be generated at the subscriber terminal unit itself. However, the text-to-speech converter is a relatively large software program and sufficient memory and processing power would have to be provided in the subscriber terminal unit to store and execute the program.

In the subscriber terminal unit, the recognizer executable code and the phoneme definitions which specify how each phoneme is recognized in terms of spectral or other signal

-60-

content are stored in read-only memory. ISP 142 determines what individual words are used in the EPG title and description or description keyword data and generates a phonemic dictionary which maps those words to phonemes. ISP 42 downloads the EPG text and vocabulary definitions to the subscriber terminal units. The EPG text and phonemic dictionary are stored in RAM of subscriber terminal unit 160. For each full EPG title, the subscriber terminal unit generates the corresponding phonemic string using the phonemic dictionary. This phonemic string is then registered with the speech recognizer as a single recognizable utterance, i.e., it becomes an atomic part of the recognizer's vocabulary. The registration includes specifying an identifier for the phonemic string, which could be a numeric value or the text for the program name. When the recognizer determines that one of the utterances in the vocabulary has been spoken, it returns the utterance identifier to the subscriber terminal unit controlling routine and permits a search of the EPG data to find occurrences of the programs having the spoken title.

The above approach to title data may also be applied to keyword data. A user may be provided with the capability of searching on keywords (e.g., actors, rating, show type, year, director, etc.) which could be marked in the text by highlighting and registered for speech recognition and corresponding database searches. This is similar to the hypertext concept. Specifically, the recognizable words would be highlighted in the program description whenever it is shown on the screen to indicate that the user may search for other shows having the same keywords. It should be mentioned that when using keywords, the phonemes for the full descriptive text does not need to be downloaded, only the phonemes for the keywords themselves.

-61-

Thus, the speech recognition interface of the subscriber terminal units which receive the EPG data and the phonemic EPG data permit the user to search the EPG data for particular shows by saying the show name, as well as permitting a search of the program description of the EPG data using the above-described keyword concept for particular actors, actresses, etc.

5 For example, if the user is tuned to television video, commanding "FIND STAR TREK" will cause a search of the EPG data to be carried out and will tune that program if it is currently available, or tune the channel where it will next be available and provide a dialog box stating when it will begin. If the user has selected the electronic programming guide grid, commanding "FIND STAR TREK" will move to the grid location where the next occurrence of the program
10 occurs. Repeating the command or saying "NEXT" will find the next subsequent instance of the program. The user can set up to record the program using the standard record from grid capabilities, i.e., saying "RECORD" will queue the program for recording and initiate the above-described display screen about how often, etc. Of course, the user can say "RECORD STAR TREK" directly from the tuned video to initiate the display screens about how often, etc.

15 As noted, the instant invention provides a hypertext-like keyword search feature. The searched keywords are part of the descriptive text for the programs as described above. The keywords are highlighted to indicate that they can be part of a search. The search can be initiated with a command such as "SEARCH KEYWORDS" which would bring up a display dedicated to that function. The user may then enter a command limiting the search, such as
20 "ONLY MARILYN MONROE", assuming "Marilyn Monroe" is a valid keyword. The screen displays the restriction and indicates how many entries in the EPG database currently match the

-62-

restriction. The user can then speak additional commands such as "ONLY MOVIES", "ONLY WITHIN 4 HOURS", "ONLY WESTERN". These commands limit the search to movies starring Marilyn Monroe which are comedies and westerns and occur within the next four hours. The screen displays these restrictions and reports how many matching items exist. When the user has created the desired list of matching items, he or she commands "SHOW LIST". This brings up a descriptive list of all matching items, if any. The user may then select an item for recording or viewing in the same manner as items from the programming guide grid. To implement this capability, ISP 142 generates a phoneme dictionary for each keyword in the same manner as it does for titles. This dictionary is then used by subscriber terminal unit 160 to tailor the vocabulary used by the speech recognition algorithm.

These searches are powerful tools which permit a user to extract very specific information from a large and complex data base using simple natural language voice commands. Of course, it will be readily apparent that this technique is not limited to subscription television systems, but may be applied in any system in which data is transmitted to a user. For example, in the case of financial data which is transmitted to a subscriber in a communication system, phoneme data representing stock identifiers may also be transmitted. This would permit a user to merely say "STOCK PRICE IBM" to generate a display of the current price of IBM stock. Another example is the use of downloaded catalogs for home shopping. By transmitting phoneme data representing different products available in the catalog, a user may say "ONLY MEN'S SUITS" to generate a display or listing of the men's suits which may be ordered from the catalog. The search could be further limited by the command "ONLY COLOR BLUE".

-63-

Another application of the search capabilities will now be discussed with reference to Figures 13A-13G. Suppose a college football fan is in a subscription television system which provides dozens of games, but the fan does not know which games are available or where to find it on the channel line-up. In accordance with the instant invention, a user activates the recognition interface and says "SEARCH." When the search screen of Figure 13A appears, the user says "ONLY FOOTBALL." The screen of Figure 13B indicates that there are 47 items which reference football in some way, i.e., football games, football documentaries, movies about football, and so on. This search is for all the items in the current program guide database, but the user only cares about football games taking place in the afternoon. Accordingly, to limit the search, the user may then say "ONLY SPORTS", after which the screen of Figure 13C indicates that there are 42 matches. The user may then say "ONLY TODAY", after which the screen of Figure 13D indicates that there are 23 matches. The user may then say "ONLY AFTER ELEVEN AM", after which the screen of Figure 13E indicates that there are 19 matches. The user may then say "ONLY BEFORE SIX PM", after which the screen of Figure 13F indicates that there are 12 matches. The user may then say "SHOW LIST" and the screen of Figure 13G displays a list of programs which satisfy the search restrictions spoken by the user.

This list is stored in the memory of the subscriber terminal unit even after the screen of Figure 13G is left. In one implementation, the creation of a new list destroys the previous list. However, it is within the scope of this invention to provide that a plurality of lists be stored in the memory of the subscriber terminal unit. When the user returns later in the day, he or she may activate the recognition interface and say "GOTO NEXT ON LIST" in order to step

-64-

through each of the currently playing programs on the list created above. In accordance with the list created above and assuming the current time is 1:30 PM, when the user says "GOTO NEXT ON LIST", the Penn State-Notre Dame game on channel 10 would be tuned. If the user says "GOTO NEXT ON LIST", the Ohio State-Michigan game on channel 5 would be tuned.

5 Whenever a program completes, it is removed from the list and the "GOTO NEXT ON LIST" command will no longer stop at the corresponding channel. Similarly, when an item on the list begins, it is added to the cycle.

When creating a list as described above, the search parameters can be specified in any order. Many useful search parameters will come from the program descriptive material in the EPG data, e.g., actor names, type of sporting event, names of teams, etc.

10

As noted, in the above discussion, EPG information provider 114-3 provides both the EPG data and the EPG phoneme data to ISP 142. However, ISP 142 may generate some or all of this EPG phoneme data using text-to-speech software programs available, for example, from VPC or Apple. In addition, the invention is not limited to EPG phoneme data. EPG template data, for example, may also be used.

15

The recognition of program titles also permits pay-per-view purchases to be made by speaking program titles as will be explained with reference to Figure 14. If a user selects the "Pay-Per-View" menu item from the main menu of Figure 12A using any of the selecting techniques described above, the pay-per-view screen of Figure 14 is displayed. This screen lists all pay-per-view programs which may be purchased for viewing by the user. The user may then select one of the programs for purchase using any of the selecting techniques described above,

20

-65-

including by speaking the title of the program. If the subscriber terminal unit is equipped with impulse-pay-per-view capabilities, billing data corresponding to the selected program may be stored in non-volatile memory and subsequently forwarded to head-end installation 125 via RF transmitter 229. Alternatively, a purchase transaction may be forwarded to head-end installation 125 via RF transmitter 229 and an authorization transaction responsive to this purchase transaction may then be forwarded to the subscriber terminal unit using any of the above-described transmission techniques. The pay-per-view operation may also be combined with the above-described keyword search techniques. Thus, the pay-per-view program list may be restricted by speaking "ONLY MOVIES", "ONLY TODAY", "ONLY SYLVESTER STALLONE", etc. as described above.

The vocabularies discussed above provide an enhanced user interface for controlling VCR 162-1 and television 162-2 by permitting a user to implement natural language control of these devices. The vocabularies also provide natural language control of the information flow from head-end installation 125. Thus, natural language is used to provide the ability to rapidly and conveniently search the large data stream. It will be appreciated that the vocabularies may be varied in accordance with the devices to be controlled. Thus, particular vocabularies for controlling electronic devices such as stereo receivers, audio cassette recorders, compact disc (CD) players, video disc players, video game players, and computers may be developed and downloaded to subscriber terminal units. Since the vocabularies are downloaded from head-end installation 125, large memories are not required for subscribers who desire a voice recognition

-66-

interface only for basic television controls. The downloaded vocabularies also permit a system operator to offer various levels of control for different service fees.

As discussed above, an enhanced speech recognition interface may be achieved by providing features which improve the recognition rate of the commands spoken by the user. Such features include a command grammar; context-based recognition logic; using "next most likely" option when a command is apparently repeated; and preferring most likely words. While the benefits of the instant invention may be achieved even if these features are not implemented, the use of these features contributes to a more user-friendly interface. Thus, a command grammar may be used to define the manner in which the command vocabulary may combined into commands for controlling the controlled device. An exemplary, but non-limiting, command grammar suitable for enhancing the voice recognition interface of the first vocabulary of Table I is VOLUME UP; VOLUME DOWN; SURF UP; and SURF DOWN. This command grammar requires that the word VOLUME must be followed by either the word UP or the word DOWN and that the word SURF must be followed by either the word UP or the word DOWN.

Thus, if a user says the words "VOLUME OFF" after activating the recognition interface, main processor 200 uses the phonemic definitions and speech recognition software to compare the spoken "VOLUME OFF" with the phonemic data of the command vocabulary. The grammar limits comparisons to valid potential words. In this case, if the recognizer recognizes the word "VOLUME", it would then compare subsequent signals only to the words "UP" and "DOWN".

Thus, "VOLUME OFF" would probably be interpreted as "VOLUME UP" since "UP" sounds

-67-

more like "OFF" than does the word "DOWN". The only case in which the recognizer would know that it has failed is when it cannot even interpret the initial word of a command.

Further, the speech recognition interface may also be configured to provide context-based recognition logic. Thus, a context-based logic can be provided which determines that a
5 command is inappropriate based upon restrictions outside the grammar. For example, a command to rewind the VCR might be correctly recognized, but be inappropriate if the VCR is not turned on. It is possible that the grammar could be continually updated to avoid such situations, but it may be easier to catch them outside the recognizer grammar. In another
10 example, suppose a user has apparently chosen channel 60, but there is no video signal available on that channel. If there is video on channel sixteen, then tuning to channel sixteen would be a good context-based action.

More sophisticated possibilities may be implemented. For example, more people watch CBS than PBS; particularly when a football game is on. If the recognizer is not sure whether the viewer has selected one or the other, CBS should be preferred. Further, the context-based
15 logic may be adaptive. If a particular household frequently tunes PBS rather than CBS, then the previous rule might be reversed. This household adaptive technique could be speaker-adaptive as well. Thus, each household member's voice could be recognized and the context-based logic tailored to them.

The "next most likely" option is based on a determination of command sequences which
20 set forth the order in which commands are given and the likelihood one command following another in these sequences.

-68-

Other variations to the invention may also be made. For example, although the speech recognition operation is shown in the above embodiments as taking place at the subscriber terminal unit, this processing could take place elsewhere in the system. One variation is shown in Figure 15 in which a transmitter 515 transmits data representing sounds or spoken words to a node 517. Sounds or spoken words are received by a subscriber terminal unit 519. The sounds or spoken words are transmitted from subscriber terminal 519 to node 517 which includes speech recognition circuitry which uses the data transmitted from transmitter 515 to generate commands according to the sounds or spoken words. Node 517 transmits the command(s) to controlled device 521 via subscriber terminal unit 519 to control controlled device 521. If this arrangement is implemented in a subscription television system, for example, node 517 may be an off-premises device connected to a plurality of subscriber terminal units which access node 517 on a time-sharing basis.

While the invention has been described in detail with reference to the appended drawings, the invention is limited in scope only by the claims. Moreover, any application cited herein should be construed to be incorporated by reference as to any subject matter deemed essential to the present disclosure.

-69-

We claim:

1. A system for controlling a device, comprising:
a first receiver for receiving utterances of a speaker;
a second receiver for receiving vocabulary data defining a vocabulary of utterances; and
5 a processor for executing a speech recognition algorithm using the received vocabulary data to recognize the utterances of the speaker and for controlling said device in accordance with the recognized utterances of the speaker.
2. The system according to claim 1, wherein the vocabulary data comprises phoneme data.
- 10 3. The system according to claim 1, wherein the vocabulary data comprises template data.
4. The system according to claim 1, wherein said first receiver is incorporated in a remote control unit.
5. The system according to claim 1, wherein said second receiver further receives
15 grammar data for defining how said vocabulary data may be used.
6. A method for controlling a device, comprising the steps of:
receiving utterances of a speaker;
receiving vocabulary data defining a vocabulary of utterances;
using the received vocabulary data to recognize the utterances of the speaker; and
20 controlling said device in accordance with the recognized utterances of the speaker.

-70-

7. The method according to claim 6, wherein the vocabulary data comprises phoneme data.
8. The method according to claim 6, wherein the vocabulary data comprises template data.
- 5 9. The method according to claim 6, wherein said first receiver is incorporated in a remote control unit.
10. The method according to claim 6, wherein said second receiver further receives grammar data for defining how said vocabulary data may be used.
11. A system for controlling access to broadcast information, comprising:
- 10 a first receiver for receiving utterances of a speaker;
- a second receiver for receiving vocabulary data defining a vocabulary of utterances; and
- a processor for executing a speech recognition algorithm using the received vocabulary data to recognize the utterances of the speaker and for controlling access to the broadcast information in accordance with the recognized utterances of the speaker.
- 15 12. The system according to claim 11, wherein the vocabulary data comprises phoneme data.
13. The system according to claim 11, wherein the vocabulary data comprises template data.
14. The system according to claim 11, wherein said first receiver is incorporated in
- 20 a remote control unit.

-71-

15. The system according to claim 11, wherein said second receiver further receives grammar data for defining how said vocabulary data may be used.

16. A method for controlling access to broadcast information, comprising the steps of:

5 receiving utterances of a speaker;

receiving vocabulary data defining a vocabulary of utterances;

using the received vocabulary data to recognize the utterances of the speaker; and

controlling access to the broadcast information in accordance with the recognized utterances of the speaker.

10 17. The method according to claim 16, wherein the vocabulary data comprises phoneme data.

18. The method according to claim 16, wherein the vocabulary data comprises template data.

15 19. The method according to claim 16, wherein said first receiver is incorporated in a remote control unit.

20. The method according to claim 16, wherein said second receiver further receives grammar data for defining how said vocabulary data may be used.

21. A system for controlling a device and for controlling access to broadcast information, comprising:

20 a first receiver for receiving utterances of a speaker;

a second receiver for receiving vocabulary data defining a vocabulary of utterances; and

-72-

a processor for executing a speech recognition algorithm using the received vocabulary data to recognize the utterances of the speaker and for controlling said device and the access to the broadcast information in accordance with the recognized utterances of the speaker.

22. The system according to claim 21, wherein the vocabulary data comprises
5 phoneme data.

23. The system according to claim 21, wherein the vocabulary data comprises template data.

24. The system according to claim 21, wherein said first receiver is incorporated in a remote control unit.

10 25. The system according to claim 21, wherein said second receiver further receives grammar data for defining how said vocabulary data may be used.

26. A method for controlling a device and for controlling access to broadcast information, comprising the steps of:

receiving utterances of a speaker;
15 receiving vocabulary data defining a vocabulary of utterances;
using the received vocabulary data to recognize the utterances of the speaker; and
controlling said device and the access to the broadcast information in accordance with the recognized utterances of the speaker.

27. The method according to claim 26, wherein the vocabulary data comprises
20 phoneme data.

-73-

28. The method according to claim 26, wherein the vocabulary data comprises template data.

29. The method according to claim 26, wherein said first receiver is incorporated in a remote control unit.

5 30. The method according to claim 26, wherein said second receiver further receives grammar data for defining how said vocabulary data may be used.

31. A system for controlling a device, comprising:

a transmitter for transmitting vocabulary data for defining a vocabulary of utterances; and
a terminal unit including:

10 a first receiver for receiving utterance data of a speaker;

a second receiver for receiving the transmitted vocabulary data; and

a processor for executing a speech recognition algorithm using the received vocabulary data to recognize utterances of the speaker and for controlling said device in accordance with the recognized utterances of the speaker.

15 32. The system according to claim 31, wherein the vocabulary data comprises phoneme data.

33. The system according to claim 31, wherein the vocabulary data comprises template data.

34. The system according to claim 31, further comprising:

-74-

a remote control unit including a microphone for receiving the utterances of the speaker and a transmitter for transmitting utterance signals representing the utterances of the speaker to said first receiver of said terminal unit as the utterance data of the speaker.

5 35. The system according to claim 34, wherein said terminal unit further comprises:
an analog front end for conditioning the utterance signals received by said first receiver;
a codec for converting the conditioned utterance signals to digital utterance signals; and
an interface for interfacing said codec to said processor.

36. The system according to claim 34, wherein said transmitter of said remote control unit comprises a radio frequency transmitter.

10 37. The system according to claim 31, further comprising:
a remote control including a microphone for receiving the utterances of the speaker, an analog receiver for conditioning utterance signals from said microphone, a codec for converting the conditioned utterance signals to digital utterance signals, and a transmitter for transmitting the digital utterance signals to said first receiver of said terminal unit as the utterance data of the
15 speaker.

38. The system according to claim 37, wherein said terminal unit further comprises:
an interface for interfacing said first receiver to said processor.

39. The system according to claim 37, wherein said transmitter of said remote control unit comprises a radio frequency transmitter.

20 40. The system according to claim 37, wherein said transmitter of said remote control unit comprises an infrared transmitter.

-75-

41. The system according to claim 31, further comprising:

a remote control including a microphone for receiving the utterances of the speaker, an analog receiver for conditioning utterance signals from said microphone, a codec for converting the conditioned utterance signals to digital utterance signals, a digital signal processor for extracting spectral information from said digital utterance signals, and a transmitter for transmitting the spectral information to said first receiver of said terminal unit as the utterance data of the speaker.

42. The system according to claim 41, wherein said terminal unit further comprises:
an interface for interfacing said first receiver to said processor.

43. The system according to claim 41, wherein said transmitter of said remote control comprises an infrared transmitter.

44. The system according to claim 31, wherein said first receiver comprises a microphone and said terminal unit further comprises:

an analog front end for conditioning utterance signals from said microphone;
a codec for converting the conditioned utterance signals to digital utterance signals; and
an interface for interfacing said codec with said processor.

45. The system according to claim 31, wherein said first receiver comprises a microphone and said terminal unit further comprises:

an analog front end for conditioning utterance signals from said microphone;
a codec for converting the conditioned utterance signals to digital utterance signals;

-76-

a digital signal processor for extracting spectral data from the digital utterance signals;
and

an interface for interfacing said digital signal processor and said processor.

46. The system according to claim 31, wherein said transmitter further transmits
5 grammar data for defining how said vocabulary data may be used.

47. A method for controlling a device, comprising the steps of:
transmitting vocabulary data for defining a vocabulary of utterances;
receiving utterance data of a speaker;
receiving the transmitted vocabulary data;
10 using the received vocabulary data to recognize utterances of a speaker; and
controlling said device in accordance with the recognized utterances of the speaker.

48. The method according to claim 47, wherein the vocabulary data is phoneme data.

49. The method according to claim 47, wherein the vocabulary data is template data.

50. A system for controlling accessing to broadcast information, comprising:
15 a transmitter for transmitting vocabulary data defining a vocabulary of utterances; and
a terminal unit including:

a first receiver for receiving utterance data of a speaker;

a second receiver for receiving the transmitted vocabulary data; and

a processor for executing a speech recognition algorithm using the received
20 vocabulary data to recognize utterances of the speaker and for controlling access to the broadcast
information in accordance with the recognized utterances of the speaker.

-77-

51. The system according to claim 50, wherein the vocabulary data comprises phoneme data.

52. The system according to claim 50, wherein the vocabulary data comprises template data.

5 53. The system according to claim 50, further comprising:

a remote control unit including a microphone for receiving the utterances of the speaker and a transmitter for transmitting utterance signals representing the utterances of the speaker to said first receiver of said terminal unit as the utterance data of the speaker.

10 54. The system according to claim 53, wherein said terminal unit further comprises:
an analog front end for conditioning the utterance signals received by said first receiver;
a codec for converting the conditioned utterance signals to digital utterance signals; and
an interface for interfacing said codec to said processor.

55. The system according to claim 53, wherein said transmitter of said remote control unit comprises a radio frequency transmitter.

15 56. The system according to claim 50, further comprising:

a remote control including a microphone for receiving the utterances of the speaker, an analog receiver for conditioning utterance signals from said microphone, a codec for converting the conditioned utterance signals to digital utterance signals, and a transmitter for transmitting the digital utterance signals to said first receiver of said terminal unit as the utterance data of the
20 speaker.

57. The system according to claim 56, wherein said terminal unit further comprises:

-78-

an interface for interfacing said first receiver to said processor.

58. The system according to claim 56, wherein said transmitter of said remote control unit comprises a radio frequency transmitter.

59. The system according to claim 56, wherein said transmitter of said remote control
5 unit comprises an infrared transmitter.

60. The system according to claim 50, further comprising:

a remote control including a microphone for receiving the utterances of the speaker, an analog receiver for conditioning utterance signals from said microphone, a codec for converting the conditioned utterance signals to digital utterance signals, a digital signal processor for
10 extracting spectral information from said digital utterance signals, and a transmitter for transmitting the spectral information to said first receiver of said terminal unit as the utterance data of the speaker.

61. The system according to claim 60, wherein said terminal unit further comprises:
an interface for interfacing said first receiver to said processor.

15 62. The system according to claim 60, wherein said transmitter of said remote control comprises an infrared transmitter.

63. The system according to claim 50, wherein said first receiver comprises a microphone and said terminal unit further comprises:

an analog front end for conditioning utterance signals from said microphone;
20 a codec for converting the conditioned utterance signals to digital utterance signals; and
an interface for interfacing said codec with said processor.

-79-

64. The system according to claim 50, wherein said first receiver comprises a microphone and said terminal unit further comprises:

an analog front end for conditioning utterance signals from said microphone;

a codec for converting the conditioned utterance signals to digital utterance signals;

5 a digital signal processor for extracting spectral data from the digital utterance signals;

and

an interface for interfacing said digital signal processor and said processor.

65. The system according to claim 50, wherein said transmitter further transmits grammar data for defining how said vocabulary data may be used.

10 66. A method for controlling access to broadcast information, comprising the steps of:

transmitting vocabulary data for defining a vocabulary of utterances;

receiving utterance data of a speaker;

receiving the transmitted vocabulary data;

15 using the received vocabulary data to recognize utterances of the speaker; and

accessing the information in accordance with the recognized utterances of the speaker.

67. The method according to claim 66, wherein the vocabulary data is phoneme data.

68. The method according to claim 66, wherein the vocabulary data is template data.

69. A system for controlling a device and for controlling access to broadcast
20 information, comprising:

a transmitter for transmitting vocabulary data defining a vocabulary of utterances; and

-80-

a terminal unit including:

a first receiver for receiving utterance data of a speaker;

a second receiver for receiving the transmitted vocabulary data; and

5 a processor for executing a speech recognition algorithm using the received vocabulary data to recognize utterances of the speaker and for controlling said device and the access to the broadcast information in accordance with the recognized utterances of the speaker.

70. The system according to claim 69, wherein the vocabulary data comprises phoneme data.

71. The system according to claim 69, wherein the vocabulary data comprises
10 template data.

72. The system according to claim 69, further comprising:

a remote control unit including a microphone for receiving the utterances of the speaker and a transmitter for transmitting utterance signals representing the utterances of the speaker to said first receiver of said terminal unit as the utterance data of the speaker.

15 73. The system according to claim 72, wherein said terminal unit further comprises:
an analog front end for conditioning the utterance signals received by said first receiver;
a codec for converting the conditioned utterance signals to digital utterance signals; and
an interface for interfacing said codec to said processor.

74. The system according to claim 72, wherein said transmitter of said remote control
20 unit comprises a radio frequency transmitter.

75. The system according to claim 69, further comprising:

-81-

a remote control including a microphone for receiving the utterances of the speaker, an analog receiver for conditioning utterance signals from said microphone, a codec for converting the conditioned utterance signals to digital utterance signals, and a transmitter for transmitting the digital utterance signals to said first receiver of said terminal unit as the utterance data of the speaker.

76. The system according to claim 75, wherein said terminal unit further comprises: an interface for interfacing said first receiver to said processor.

77. The system according to claim 75, wherein said transmitter of said remote control unit comprises a radio frequency transmitter.

78. The system according to claim 75, wherein said transmitter of said remote control unit comprises an infrared transmitter.

79. The system according to claim 69, further comprising:

a remote control including a microphone for receiving the utterances of the speaker, an analog receiver for conditioning utterance signals from said microphone, a codec for converting the conditioned utterance signals to digital utterance signals, a digital signal processor for extracting spectral information from said digital utterance signals, and a transmitter for transmitting the spectral information to said first receiver of said terminal unit as the utterance data of the speaker.

80. The system according to claim 79, wherein said terminal unit further comprises: an interface for interfacing said first receiver to said processor.

-82-

81. The system according to claim 79, wherein said transmitter of said remote control comprises an infrared transmitter.

82. The system according to claim 69, wherein said first receiver comprises a microphone and said terminal unit further comprises:

5 an analog front end for conditioning utterance signals from said microphone;
 a codec for converting the conditioned utterance signals to digital utterance signals; and
 an interface for interfacing said codec with said processor.

83. The system according to claim 69, wherein said first receiver comprises a microphone and said terminal unit further comprises:

10 an analog front end for conditioning utterance signals from said microphone;
 a codec for converting the conditioned utterance signals to digital utterance signals;
 a digital signal processor for extracting spectral data from the digital utterance signals;
and
 an interface for interfacing said digital signal processor and said processor.

15 84. The system according to claim 69, wherein said transmitter further transmits grammar data for defining how said vocabulary data may be used.

85. A method for controlling a device and for controlling access to broadcast information, comprising the steps of:

20 transmitting vocabulary data for defining a vocabulary of utterances;
 receiving utterance data of a speaker;
 receiving the transmitted vocabulary data;

-83-

using the received vocabulary data to recognize utterances of the speaker; and
controlling said device and the access to the information in accordance with the
recognized utterances of the speaker.

86. The method according to claim 85, wherein the vocabulary data is phoneme data.

5 87. The method according to claim 85, wherein the vocabulary data is template data.

88. A system for controlling a television receiver to allow user selection of broadcast
programs from program schedule information, comprising:

a first receiver for receiving the program schedule information;

a second receiver for receiving utterances of the user; and

10 a processor for executing a speech recognition algorithm to recognize the utterances of
the user and for selecting broadcast programs from the program schedule information in
accordance with the recognized utterances of the user.

89. The system according to claim 88, further comprising:

a tuner for tuning channels carrying the broadcast programs,

15 wherein said processor generates a tuner control signal for controlling said tuner to tune
channels corresponding to selected broadcast programs.

90. The system according to claim 88, wherein said first receiver further receives
vocabulary data for defining a vocabulary of recognized utterances.

20 91. The system according to claim 90, wherein the program schedule information
includes program titles and the vocabulary data defines a vocabulary of recognized utterances
which includes the program titles, whereby the speech recognition algorithm recognizes spoken

-84-

program titles and the broadcast programs are selectable from the program schedule information in accordance with recognized program titles.

92. The system according to claim 90, wherein the program schedule information includes program description keywords and the vocabulary data defines a vocabulary of
5 recognized utterances which includes the program description keywords, whereby the speech recognition algorithm recognizes spoken program description keywords and the broadcast programs are selectable from the program schedule information in accordance with recognized program description keywords.

93. The system according to claim 88, further comprises:
10 means for displaying the program schedule information on said television receiver.

94. The system according to claim 93, wherein the vocabulary data defines a vocabulary of recognized utterances which includes navigation commands, whereby the speech recognition algorithm recognizes spoken navigation commands and said processor navigates the displayed program schedule information in accordance with recognized navigation commands.

15 95. A remote control for transmitting utterance data to a receiver, comprising:
a microphone for receiving utterances of a speaker;
an analog-to-digital converter for converting utterance signals from said microphone to digital utterance signals;
a digital signal processor for extracting time-variant spectral characteristics of said digital
20 utterance signals; and
a transmitter for transmitting the time-variant spectral characteristics to said receiver.

-85-

96. The remote control according to claim 95, further comprising:

an analog front end for conditioning utterance signals from said microphone and supplying conditioned utterance signals to said analog-to-digital converter.

97. The remote control according to claim 95, wherein said transmitter comprises an
5 infrared transmitter.

98. The remote control according to claim 95, wherein said transmitter transmits the time-variant spectral characteristics at a data rate less than 10k bits per second.

99. A subscription television system, comprising:

a head-end installation for transmitting vocabulary data for defining a vocabulary of
10 spoken commands;

a subscriber terminal unit connected to a television, said subscriber terminal unit including:

a first receiver for receiving spoken command data;

a second receiver for receiving the vocabulary data transmitted from said head-end
15 installation; and

a processor for executing a speech recognition algorithm using the vocabulary data to recognize spoken commands and for controlling said television in accordance with the recognized spoken commands.

100. The subscription television system according to claim 99, wherein the vocabulary
20 data comprises phoneme data.

-86-

101. The subscription television system according to claim 99, wherein the vocabulary data comprises template data.

102. The subscription television system according to claim 99, wherein the vocabulary data defines a vocabulary of spoken commands which includes at least one command selected
5 from the groups of commands consisting of: powering on said television; powering off said television; tuning said television to a channel; increasing volume; and decreasing volume.

103. The subscription television system according to claim 99, wherein said head-end installation further transmits electronic programming guide information and said second receiver further receives the transmitted electronic programming guide data.

104. The subscription television system according to claim 103, wherein the vocabulary
10 data defines a vocabulary of recognized commands for accessing the electronic programming guide data.

105. The subscription television system according to claim 103, wherein the electronic programming guide information is displayed on said television in a grid having rows defined by
15 channels and columns defined by time and the vocabulary data defines a vocabulary of recognized commands which includes moving commands for moving in said grid.

106. The subscription television system according to claim 105, wherein the vocabulary data defines a vocabulary of recognized commands which further includes a record command for recording a program identified in said grid.

-87-

107. The subscription television system according to claim 105, wherein the vocabulary data defines a vocabulary of recognized commands which further includes a tune command for tuning to a program identified in said grid.

5 108. The subscription television system according to claim 105, wherein the vocabulary data defines a vocabulary of recognized commands which further includes an information command for displaying information regarding a program identified in said grid.

109. The subscription television system according to claim 105, wherein the vocabulary data defines a vocabulary of recognized commands which further includes program titles, whereby a program in said grid is selectable by title.

10 110. An information broadcasting center for broadcasting information to at least one terminal unit, comprising:

first transmitting means for transmitting text information; and

second transmitting means for transmitting phonemic data corresponding to at least a portion of the text information.

15 111. The information broadcasting center according to claim 110, further comprising:

first receiving means for receiving the text information and supplying the received text information to said first transmitting means; and

second receiving means for receiving the phonemic data and supplying the received phonemic data to said second transmitting means.

20 112. The information distribution center according to claim 110, further comprising:

-88-

first receiving means for receiving the text information and supplying the received text information to said first transmitting means; and

a text-to-phoneme translator for translating at least a portion of the received text information into phonemic data and supplying the phonemic data to said second transmitting means.

113. The information distribution center according to claim 110, wherein said text information comprises electronic programming guide data.

114. A subscriber terminal unit, comprising:


a tuner for tuning channels of a television signal, each channel carrying a respective program identified by a program title;

a memory for storing a speech recognition algorithm for recognizing spoken program titles; and

a processor for executing the speech recognition algorithm to recognize a program title spoken by a subscriber and for generating a tuner control signal for controlling said tuner to tune to the channel carrying the program corresponding to the recognized program title.

1/28

FIG. 1



2/28

FIG. 2A





FIG. 2B



4/28

FIG. 2C





FIG. 3



6/28

FIG. 4






FIG. 5




8/28

FIG. 6




9/28

FIG. 7




10/28


FIG. 8



11/28

FIG. 9

12/28

FIG. 10**FIG. 11**

64		60		
03/05	7:00 PM	7:30 PM	8:00 PM	8:30 PM
WXIA 14	HOLLYWO SQUARES	GILLIGANS ISLAND	BRADY BUNCH	TOM AND JERRY
HBO 15	TERMINATOR 2 [R] [CC]		HOME ALONE [PG] [CC]	
62	KABC 16	TERMINA- TOR 2	WRESTLING	
ESPN 17	GOLF	WIMBLEDON		BOWLING
SHOW 18	BAD NEWS BEARS [PG]			CITIZEN KANE
TMC 19	ONE GOOD COOP [R]			INVISIBLE MAN
CURRENT TIME: 7:15 PM CURRENT DATE: 03/05				
PRESS [INFO] FOR DETAILS, [SELECT] TO TUNE. PRESS [MENU] TO EXIT.				

FIG. 12A

MAIN MENU

1. PAY PER VIEW
2. WHAT'S ON CABLE
3. MESSAGES/INFORMATION
4. FAVORITE CHANNELS
5. VCR PROGRAM TIMER
6. SLEEP TIMER
7. PARENTAL CONTROL
8. CABLE TERMINAL SETUP
9. EXIT

PLEASE MAKE SELECTION.

FIG. 12B

WHAT'S ON CABLE

1. VIEWING CHANNEL
2. FAVORITE CHANNEL
3. CHANNEL LISTINGS
4. CATEGORIES
5. EXIT

PLEASE MAKE SELECTION.

14/28

FIG. 12C

VIEWING GUIDE

1. TUNE TV TO PROGRAM
2. RECORD PROGRAM
3. PROVIDE INFORMATION
ON PROGRAM
4. EXIT

PLEASE MAKE SELECTION.

FIG. 12D

YOU'VE CHOSEN:
ESPN CH 17
SEE THE WORLD'S FINEST GOLFER'S
IN FIRST ROUND ACTION AT THE
U.S. OPEN.
STARTS: 7:00PM ENDS: 7:30PM

RECORD:

1. ONE-TIME
2. DAILY
3. WEEKLY
4. EXIT

PLEASE MAKE SELECTION.

15/28

FIG. 12E

<p>VCR IS SCHEDULED TO RECORD:</p> <p>1. 3/5/94 CH 17 7:00 PM TO 7:30PM</p>

FIG. 12F

FAVORITE CHANNEL GUIDE				
	7:00 PM	7:30 PM	8:00 PM	8:30 PM
KABC 16	TERMIN- ATOR 2	WRESTLING		
ESPN 17	GOLF	WIMBELDON	BOWLING	
DIS 29	JEOPARDY	NATIONAL GEOGRAPHIC	MICKEY MOUSE	
CURRENT TIME: 6:51 PM			DATE: 3/5/94	

16/28

FIG. 12G

14	WXIA	19	TMC
15	HBO	29	DIS
16	KABC		
17	ESPN		
18	SHOW		

1. VIEWING GUIDE
2. MAIN MENU
3. EXIT

PLEASE MAKE SELECTION.

FIG. 12H

CATEGORIES

1. CHILDREN/EDUCATION/SCIENCE
2. DRAMA/ROMANCE
3. ENTERTAINMENT/VARIETY
4. MOVIES
5. NEWS/TALK/MAGAZINE
6. SPECIALS/MINI-SERIES
7. PRE-RECORDED SPORTS
8. LIVE SPORTS
9. ACTION/MYSTERY/HORROR
10. COMEDY
11. MISCELLANEOUS
12. EXIT

PLEASE MAKE SELECTION.

17/28

FIG. 12I

LIVE SPORTS	
1.	BASEBALL
2.	BASKETBALL
3.	SOCCER
4.	MORE LISTINGS
5.	EXIT
PLEASE MAKE SELECTION.	

FIG. 12J

BASEBALL	
CH	PROGRAM NAME
1. 02	CUBS vs METS
2. 07	BRAVES vs REDS
3. EXIT	
PLEASE MAKE SELECTION.	

18/28

FIG. 12K

VCR PROGRAM TIMER

1. USE PLUS CODES
2. SET PROGRAM TIMER
3. CHANGE PROGRAM TIMER
4. CLEAR PROGRAM TIMER
5. EXIT

PLEASE MAKE SELECTION.

FIG. 12L

PLUS CODES

STATE THE CODE ONE DIGIT
AT A TIME

STATE "OK" WHEN YOU ARE DONE.
STATE "EXIT" TO EXIT.

19/28

FIG. 12M

PROGRAM TIMER

1. EPG PROGRAM VCR
2. VOICE PROGRAM VCR
3. EXIT

PLEASE MAKE SELECTION.

FIG. 12N

- 1.
- 2.
- 3.
- 4.
- 5.

SELECT PROGRAM NUMBER.

20/28

FIG. 120

STATE "DAY"
EXAMPLE: SATURDAY

FIG. 12P

PROGRAM 1
RECORD ON JUNE 11, 1994
STATE:
"START HOUR, START MINUTE,
AM OR PM"
EXAMPLE: "EIGHT ZERO ZERO PM"

21/28

FIG. 12Q

START TIME: 9:05 PM

STATE:

"STOP HOUR, STOP MINUTE, AM OR PM"

FIG. 12R

STOP TIME: 10:35 PM

STATE: CHANNEL

22/28

FIG. 12S

PROGRAM 1

START TIME: 9:05 PM
STOP TIME: 10:35 PM
DATE: JUNE 11, 1994
CHANNEL: 07
SPEED
1. SP
2. EP
3. LP

PLEASE MAKE SELECTION.

FIG. 12T

PROGRAM 1

START TIME: 9:05 PM
STOP TIME: 10:35 PM
DATE: JUNE 11, 1994
CHANNEL: 07
SPEED: SP

STATE "OK" IF THIS
INFORMATION IS CORRECT.

23/28

FIG. 12U

YOUR VCR WILL TAPE THE
PROGRAMMING ON:

JUNE 11, 1994
FROM 9:05 TO 10:35 PM
ON CH 07
AT SP SPEED

24/28

FIG. 13A

SEARCH...

FIG. 13B

SEARCH...
ONLY FOOTBALL

47 ITEMS HAVE BEEN FOUND.

25/28

FIG. 13C

SEARCH...
ONLY FOOTBALL
ONLY SPORTS

42 ITEMS HAVE BEEN FOUND.

FIG. 13D

SEARCH...
ONLY FOOTBALL
ONLY SPORTS
ONLY TODAY

23 ITEMS HAVE BEEN FOUND.

26/28

FIG. 13E

SEARCH...

ONLY FOOTBALL
ONLY SPORTS
ONLY TODAY
ONLY AFTER ELEVEN AM

19 ITEMS HAVE BEEN FOUND.

FIG. 13F

SEARCH...

ONLY FOOTBALL
ONLY SPORTS
ONLY TODAY
ONLY AFTER ELEVEN AM
ONLY BEFORE SIX PM

12 ITEMS HAVE BEEN FOUND.

27/28

FIG. 13G

LIST

1. PENN STATE - NOTRE DAME
CHANNEL 10 12:30 PM
2. OHIO STATE - MICHIGAN
CHANNEL 5 1:00 PM
3. ~~~~~
4. ~~~~~
5. MORE
6. EXIT

PLEASE MAKE SELECTION.


FIG. 14

PAY-PER-VIEW

1. TERMINATOR 2
2. FORREST GUMP
3. THE LION KING
4. PULP FICTION
5. SPEED
6. MORE
7. EXIT

PLEASE MAKE SELECTION.


FIG. 15



PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G10L 9/00, 3/00, 5/02, 5/06	A3	(11) International Publication Number: WO 96/21990 (43) International Publication Date: 18 July 1996 (18.07.96)
(21) International Application Number: PCT/US96/00246 (22) International Filing Date: 3 January 1996 (03.01.96) (30) Priority Data: 08/367,997 3 January 1995 (03.01.95) US (71) Applicant: SCIENTIFIC-ATLANTA, INC. [US/US]; One Technology Parkway South, Norcross, GA 30092 (US). (72) Inventors: HOUSER, Peter, B.; 14574 High Pine Street, Poway, CA 92064 (US). SCHUTTE, Mark, E.; 4570 Browning Trail, Sugar Hill, GA 30518 (US). MAGID, Gloria, J.; 13810 Riverhead Court, San Diego, CA 92129 (US). (74) Agents: SHEA, Michael, J. et al.; Banner & Allegretti, Ltd., 11th floor, 1001 G Street N.W., Washington, DC 20001 (US).		(81) Designated States: AL, AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AZ, BY, KZ, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> (88) Date of publication of the international search report: 26 September 1996 (26.09.96)

(54) Title: INFORMATION SYSTEM HAVING A SPEECH INTERFACE**(57) Abstract**

A system (10) for controlling a device and for controlling access to broadcast information (14(1)-14(n)) is disclosed. The system includes a first receiver for receiving utterances of a speaker, a second receiver for receiving vocabulary data defining a vocabulary of utterances, and a processor for executing a speech recognition algorithm using the received vocabulary data to recognize the utterances of the speaker and for controlling the device and the access to the broadcast information in accordance with the recognized utterances of the speaker.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US96/00246

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : G10L 9/00, 3/00, 5/02, 5/06

US CL : 395/2.84, 2.79, 2.38, 2.39, 2.6

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 395/2.84, 2.79, 2.38, 2.39, 2.6

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
APS, DERWENT, DIALOG

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US, A, 5,086,385 (LAUNEY ET AL.) 04 FEBRUARY 1992, Fig. 1, col. 4, lines 30-33.	1-114
X	Dawson, "TIME WARNER PURSUES VOICE AS A NEW REMOTE", Multichannel News, 09 January 1995, pages 31 and 34.	1-114
Y	US, A, 5,157,760 (AKAGIRI) 20 OCTOBER 1992, Fig. 1.	1-114
X	US, A, 5,335,313 (DOUGLAS) 02 AUGUST 1994, Fig. 1.	1-114
X	US, A, 5,334,276 (THOMPSON ET AL.) 02 AUGUST 1994, Fig. 1.	1-114
Y	US, A, 4,706,121 (YOUNG) 10 NOVEMBER 87, Fig. 1.	1-114

☒ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be part of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier document published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search
24 MAY 1996

Date of mailing of the international search report

26 JUN 1996

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Authorized officer

JOHN MICHAEL GROVER

Facsimile No. (703) 305-3230

Telephone No. (703) 305-9600

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US96/00246

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US, A, 5,353,121 (YOUNG ET AL.) 04 OCTOBER 1994, Fig. 1.	1-114
Y	US, A, 5,267,323 (KIMURA) 30 NOVEMBER 1993, Fig. 1.	1-114
Y	US, A, 5,230,023 (NAKANO) 20 JULY 1993, Fig. 1.	1-114